



L.O.A. w/pulpit	21'9" (6.63m)
Hull length	20'3" (6.17m)
Beam	8'3" (2.51m)
Dry weight w/135 O/B (approx.)	3200 lbs. (1451kg)
Fuel capacity (Gas)	75 gal. (283.8L)
Max power @ prop	225 HP (167.8kw)
Shaft length	25" (.64m)
Deadrise	19°
Draft: up (approx.)	15" (.40m)
Draft: down (approx.)	31" (.79m)
Bridge clearance w/o top	4'9" (1.45m)
Bridge clearance w/bimini top	6'9" (2.05m)

KEY SALES FEATURES

- Bow pulpit Full height transom
- Fiberglass stringer system composite transom
- Versatile bowrider suited for fishing, skiing or diving
- Symmetrical consoles port/stbd with storage
 Rod storage under gunnel
 Ski and kneeboard storage
 - All stainless steel deck hardware thru-bolted
 - Location for ski pylon
 - 10-year structural hull warranty transferable
 - · Complies with Coast Guard safety regulations
 - NMMA Certified Diamond pattern skid resistant fiberglass deck for easy maintenance

STANDARD EQUIPMENT

HULL & DECK

Anchor locker

Bow pulpit with roller and deck pipe Bow and stern eyes - stainless steel Cleats - stainless steel thru-bolted

Gunnel caps - coated aluminum Rod holders - 2 stainless steel flush mount with cap Stainless steel rails

Swim platform - integrated with stainless steel ladder Transom - full height with door Windshield - walk-thru -

tempered glass

<u>COCKPIT</u> Beverage holders (5)

Cockpit overboard scuppers Cooler - 56 qt built-in - port helm Courtesy lights Fish boxes - two insulated 40 qt. with overboard pumpout

Forward seating area with storage with port/stbd cushions

Helm storage

Pedestal seats - with cushions (2) Rod storage racks under gunnel Ski locker with hinged lid Tackle storage box

MECHANICÁL

Accessory plug - 12V Bilge pump w/auto float switch Compass Horn

Ignition - safety interlock system with lanyard

Instrumentation - tachometer, fuel, volts, water pressure,trim and speedometer

Navigation lights Power for electronics at helm Propeller - aluminum Remote oil fill

Steering - tilt hydraulic Steering wheel - stainless steel Switches - weather resistant Trailer - galvanized

* Drop shipped engines only

OPTIONAL EQUIPMENT

Battery switch - dual with trays Bimini top - Sunbrella Bow cover - Sunbrella

Canada certification

CE certification (for export only)

Cockpit carpet - snap in (available with ski package only)

Cradle

Port lounge seat with storage box Pre-rig for Merc, Yamaha, Evinrude, and Johnson

(Recommended HP: 135 hp to

225 hp, check for engine availability) Stainless steel rubrail insert

Trailer - aluminum

Canvas Package 1

Side and aft curtains, windshield connector

* Canvas Package 2 Side and drop curtains,

windshield connector

Tournament Edition Blue (NEW) Custom graphics

Cockpit bolsters (port/stbd) Custom steering wheel

Stainless steel thru hulls

* Tournament Edition Gold (NEW)

Custom graphics Cockpit bolsters (port/stbd) Custom steering wheel

Stainless steel thru hulls

Saltwater Fish Package Aft seat with aft bolsters Heavy duty dive ladder - removable

Raw water washdown

Ski Package Aft seat with aft bolsters Bow filler cushion

Heavy duty dive ladder - removable Port lounge seat with storage box Pressurized fresh water system

with transom shower (8 gal.) Ski pylon

Stereo AM/FM CD player with 4 speakers

Upholstered helm seat with livewell

* Note: Items in Packages cannot be ordered individually.

ENGINE OPTIONS

Merc 150 XL Saltwater Classic Merc 150 XL Optimax Saltwater (DIG) Merc 200 XL Optimax Saltwater (DIG)

Johnson 150 Evinrude 150 FFI Evinrude 200 FFI Yamaha 150 TXRA Yamaha Z 150 TXRA Yamaha Z 200 TXRA Yamaha F 200 TXRA Yamaha F 225 TXRA

PERFORMANCE DATA - 225 O/B

Time to Plane Top Speed Cruise Speed Cruise Range

3.02 Seconds 48.9 MPH @ 5520 RPM 31.6 MPH @ 4000 RPM 154 Miles

Performance and fuel consumption will vary and be affected by water and weather conditions, altitude, load and condition of boat, engine and propeller(s). Cruise range based on 95% of fuel capacity. All data is illustrative and is not warranted. Performance data based on 225 hp engine.

Specifications, options, and equipment are subject to change without notice.