



WELLCRAFT 2019

PRODUCT INFORMATION GUIDE



A SUPERIOR CRAFT REINVENTED FOR EVERYONE

Since 1955, Wellcraft® has stood for innovation, quality, and reliability. These core values are found in an American icon reinforced to the forefront of all-purpose boating. From offshore fishing to Great Lakes touring, the journey begins with a turn of the key.

Such capability is thoroughly expressed in the ability to deliver features anglers crave alongside the creature-comforts families desire. Boats of this caliber are reflected through expert craftsmanship and revolutionary engineering entrusted into every series and model.

Legendary performance is a given. A passion for style is required, and its execution is vital. Welcome aboard Wellcraft.



182 Fisherman	6-11
202 Fisherman	12-17
222 Fisherman	18-23
242 Fisherman	24-29
262 Fisherman	30-37
302 Fisherman	38-43
352 Fisherman	44-51
221 Bay	54-59
241 Bay	60-65
Trailers	66-71
Warranty	72-82

Notice: Wellcraft specifications, photography, video, features, and options are for reference purposes only. Models are shown with non-Wellcraft options and accessories. Options vary by model while some are shown with optional equipment. While Wellcraft makes every effort to ensure information contained herein is correct, content should not be regarded as infallible as unending product refinement and design changes may result in revisions to current models. Wellcraft reserves the right to change product specifications, models, features, imagery, video, and colors at any time without notification or incurring obligations. Representations herein do not constitute a warranty of any of the products shown. All limited warranties are outlined in the Wellcraft limited warranty that accompanies each boat. Please see your authorized Wellcraft dealer for additional information, option availability, and specific warranty details prior to purchase.



Wellcraft

FISHERMAN



182 FISHERMAN



SPECIFICATIONS	US	METRIC
L.O.A.	18' 2"	5.59 m
Beam	8' 0"	2.44 m
Fuel Capacity	56 gal	212 L
Draft Up	15"	38 cm
Draft Down	32"	81 cm
Maximum Capacity	2,000 lbs	907 kg
Persons Capacity	8	7 CE
Approx. Boat Weight	2,200 lbs	998 kg
Approx. Boat & Engine Weight	2,750 lbs	1,247 kg
Max HP	150 hp	112 kw
Deadrise	19°	19°
Bridge Clearance	5' 10"	1.78 m
Bridge Clearance w/T-Top	7' 3"	2.21 m
Keel to Top of T-Top	8' 6"	2.59 m
Keel to Top of Windshield	7' 1"	2.16 m
Trailer Height w/T-Top	10' 1"	3.07 m
Trailer Height w/o T-Top	8' 8"	5.69 m

POWER RATINGS & WEIGHTS

Engine Type	Propshaft Power		Boat & Engine Weight	
	HP	KW	LBS	KG
Mercury® 90EXLPT CT FourStroke	90	67	2600	1180
Mercury® 115EXLPT FourStroke	115	86	2600	1180
Mercury® 150 XL FourStroke	150	112	2700	1225
Yamaha® F90XB	90	67	2600	1180
Yamaha® F115XB	115	86	2625	1190
Yamaha® F150XB	150	112	2750	1250



182F

PERFORMANCE

Power HP/KW	Propeller (Dia x Pitch)		Type	Top Speed		Cruise Range	
	IN	CM		MPH	KPH	MI	KM
Mercury® 90EXLPT CT FourStroke	15x15	38x38	SST	32-35	51-56	212	341
Mercury® 115EXLPT FourStroke	13.4x15	34x38	AL	35-38	56-61	228	367
Mercury® 150 XL FourStroke	14.5x17	37x43	SST	42-46	68-74	202	325
Yamaha® F90XB	13.5x14	34x36	AL	32-35	51-56	273	439
Yamaha® F115XB	13.5x15	34x38	AL	35-38	56-61	252	406
Yamaha® F150XB	14.25x17	36x43	SST	42-46	68-74	223	359

FUEL FLOW DATA - 182F - MERCURY® 90EXLPT CT FOURSTROKE

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
1500rpm	5	8	1	4
2000rpm	6	10	2	6
2500rpm	7	11	2	8
3000rpm	8	13	3	11
3500rpm	10	16	5	18
4000rpm	18	30	5	19
4500rpm	23	37	6	22
5000rpm	27	44	7	26
5500rpm	31	49	8	30
WOT	33	53	9	32

FUEL FLOW DATA - 182F - MERCURY® 115EXLPT FOURSTROKE

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
1500rpm	6	9	1	3
2000rpm	7	11	1	5
2500rpm	8	12	2	9
3000rpm	9	14	3	13
3500rpm	11	17	5	17
4000rpm	20	33	5	18
4500rpm	26	41	6	22
5000rpm	30	48	7	28
5500rpm	34	54	9	35
WOT	36	58	11	41

FUEL FLOW DATA - 182F - MERCURY® 150 XL FOURSTROKE

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
1500rpm	7	11	1	4
2000rpm	8	13	2	7
2500rpm	9	15	3	12
3000rpm	10	17	5	17
3500rpm	13	20	7	26



4000 rpm	24	39	6	24
4500 rpm	30	49	8	30
5000 rpm	36	57	10	38
5500 rpm	40	65	13	48
WOT	43	69	15	55

FUEL FLOW DATA - 182F - YAMAHA® F90XB

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
1500 rpm	4	7	1	3
2000 rpm	5	9	1	4
2500 rpm	6	10	2	7
3000 rpm	7	12	3	10
3500 rpm	10	15	4	15
4000 rpm	19	30	4	14
4500 rpm	24	39	5	17
5000 rpm	28	45	6	22
5500 rpm	31	50	7	28
WOT	34	55	9	32

FUEL FLOW DATA - 182F - YAMAHA® F115XB

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
1500 rpm	5	8	1	3
2000 rpm	6	10	1	5
2500 rpm	7	11	2	8
3000 rpm	8	13	3	12
3500 rpm	11	17	5	17
4000 rpm	21	33	5	17
4500 rpm	27	43	6	21
5000 rpm	31	50	7	26
5500 rpm	35	56	9	33
WOT	37	60	10	38

FUEL FLOW DATA - 182F - YAMAHA® F150XB

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
1500 rpm	6	9	1	5
2000 rpm	7	11	2	7
2500 rpm	8	12	3	12
3000 rpm	11	18	5	18
3500 rpm	22	35	5	20
4000 rpm	27	43	6	24
4500 rpm	32	51	8	30
5000 rpm	36	58	10	37
5500 rpm	40	65	13	49
WOT	44	70	16	59

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Impeller, Boat Bottom Condition, and Operator Technique.



STANDARDS

HULL AND DECK

Anchor locker/storage
Bow and stern Eyes, stainless steel
Cleats, stainless steel
Fiberglass floor liner
Fiberglass stringer system
Flotation Foam
Gel scheme, all white
Horn, stainless steel
Ladder, boarding, fixed
Meets applicable USCG & Canadian Regs;
 NMMA Certified using ABYC STDs.
Navigation Lights
Rod holders, gunnel mount
Rub Rail, w/stainless steel insert
Thru hull fittings, stainless steel
Winning Edge Protection Plan

COCKPIT

Assist handles, stainless steel
Baitwell/live well, 17 gallon w/bluecoat,
 aquarium style, insulated
Beverage holder(s), synthetic
Cockpit Interior, choice of
 Carbon Fiber, Cognac,
 Neutral w/Black Accent, or Seaside
Courtesy lights
Cutting station, aft
Diamond pattern non-skid
Leaning post w/backrest, folding
Rod storage, gunnel
Seating, aft folding bench
Seating, forward console
Self bailing cockpit
Storage, bow

HELM

12 volt receptacle
Cell Phone Holder
Steering Wheel w/knob, stainless steel
USB charge port

ENGINE / SYSTEMS / DRIVE

Battery tray(s)
Bilge pump, automatic

CONSOLE

Changing room
Head floor, fiberglass liner
Windscreen, console,
 removable

TRAILER

Wellcraft custom trailer, single axle
Galv/Gatorhyde



OPTIONS	
HULL AND DECK Anchor w/rope & chain Gel scheme, solid color hull or two-tone, choice of Crimson Red, Denim Blue, Jet Black, Liquid Blue, Phantom Grey, or Seafoam Green Gel scheme, tri-tone, choice of Black/Atomic, Black/Crimson Red, Black/Phantom Grey, Black/White, or White/Black Rod holders, pair, *requires T-top (clamp on) Underwater lights	CONSOLE Head, porta pottie (NA Canada) Head, pump-out
TOW SPORTS Ski tow pylon, removable	T-TOPS T-Top, White Frame w/canvas enclosure
COCKPIT Cockpit Reed Flooring, Ash or Dune Cooler, carry-on, 72qt. Transom cutting board w/tool holders	CANVAS Bimini Top (NA w/T-Top) Console cover Sail Shade w/Carbon Fiber Poles
ENTERTAINMENT Stereo System: AM/FM w/Bluetooth* USB & MP3 port Speakers (2)	TRAILER EZ-loader aluminum, single axle w/brakes & spare Spare tire, aluminum or galvanized Trailer delete Wheels, aluminum
HELM Compass GPS plotter w/depth sounder, Garmin 741XS	PACKAGES Bow Seating Package Bow seat cushions Mat Package Bow pads Coaming pads Head door pad Helm footrest mat Offshore Package Logos & Designators, Black Mat Package, Kryptek Offshore Graphics, Black or White Stainless Steel Upgrade Package Grab handles Cleats-pull up Beverage Holders Aft rod/beverage holder combo (2)
ENGINE / SYSTEMS / DRIVE Battery charger Battery charger w/trolling motor pre-wire Battery on/off switch Down rigger pre-wire Hydraulic steering (STD on 150 hp and up) Hydraulic tilt steering (90 & 115 hp only) Raw water wash down Trim tabs w/LED Indicators Trolling motor pre-wire VesselView Mobile, Mercury	



NOTES



202 FISHERMAN



SPECIFICATIONS	US	METRIC
L.O.A.	20' 4"	6.2 m
Beam	8' 6"	2.54 m
Fuel Capacity	56 gal	212 L
Draft Up	17"	43 cm
Draft Down	33"	84 cm
Maximum Capacity	2,350 lbs	1,066 kg
Persons Capacity	8	8 CE
Approx. Boat Weight	2,650 lbs	1,202 kg
Approx. Boat & Engine Weight	3,100 lbs	1,406 kg
Max HP	200 hp	150 kw
Deadrise	19°	19°
Bridge Clearance	5' 8"	1.73 m
Bridge Clearance w/T-Top	7' 4"	2.24 m
Keel to Top of T-Top	8' 6"	2.59 m
Keel to Top of Windshield	7' 1"	2.16 m
Trailer Height w/T-Top	10' 1"	3.07 m
Trailer Height w/o T-Top	8' 8"	2.64 m

POWER RATINGS & WEIGHTS

Engine Type	Propshaft Power		Boat & Engine Weight	
	HP	KW	LBS	KG
Mercury® 115EXLPT CT FourStroke	115	86	3075	1395
Mercury® 150XL FourStroke	150	112	3150	1429
Mercury® 200XL FourStroke DTS	200	149	3225	1463
Yamaha® F115XB	115	86	3100	1406
Yamaha® F150XB	150	112	3200	1451
Yamaha® F200XB	200	149	3200	1451



202F

PERFORMANCE

Power HP/KW	Propeller (Dia x Pitch)		Type	Top Speed		Cruise Range	
	IN	CM		MPH	KPH	MI	KM
Mercury® 115EXLPT CT FourStroke	15 x 17	38 x 43	AL	34-37	55-60	223	359
Mercury® 150XL FourStroke	14.5 x 15	37 x 38	SS	39-42	63-68	183	295
Mercury® 200XL FourStroke DTS	15.5 x 17	39 x 43	SS	43-46	69-74	149	240
Yamaha® F115XB	13.625 x 14	35 x 36	AL	34-37	55-60	327	526
Yamaha® F150XB	14.5 x 15	37 x 38	SS	39-42	63-68	223	359
Yamaha® F200XB	14.5 x 15	37 x 38	SS	43-46	69-74	240	386

FUEL FLOW DATA - 202F - MERCURY® 115EXLPT CT FOURSTROKE

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
1500rpm	5	8	1	4
2000rpm	7	10	1	5
2500rpm	8	12	2	8
3000rpm	10	16	3	11
3500rpm	15	24	4	15
4000rpm	21	34	5	19
4500rpm	25	40	6	23
5000rpm	29	46	7	28
5500rpm	32	52	9	34
WOT	36	58	11	41

FUEL FLOW DATA - 202F - MERCURY® 150XL FOURSTROKE

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
1500rpm	6	9	1	5
2000rpm	7	12	2	7
2500rpm	9	14	3	11
3000rpm	11	18	4	15
3500rpm	17	27	5	20
4000rpm	23	37	7	25
4500rpm	28	45	8	31
5000rpm	32	52	10	37
5500rpm	36	58	12	46
WOT	40	64	15	55

FUEL FLOW DATA - 202F - MERCURY® 200XL FOURSTROKE DTS

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
1500rpm	7	10	2	7
2000rpm	8	13	3	10
2500rpm	10	15	4	16
3000rpm	12	20	6	21
3500rpm	19	30	7	28



4000 rpm	26	42	9	36
4500 rpm	31	50	11	43
5000 rpm	36	58	14	52
5500 rpm	40	65	17	63
WOT	45	72	20	76

FUEL FLOW DATA - 202F - YAMAHA® F115XB

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
1500 rpm	5	8	1	3
2000 rpm	6	9	1	5
2500 rpm	7	11	2	7
3000 rpm	9	15	2	9
3500 rpm	18	30	3	11
4000 rpm	23	37	4	14
4500 rpm	26	42	5	18
5000 rpm	30	48	6	24
5500 rpm	33	53	8	31
WOT	36	57	10	38

FUEL FLOW DATA - 202F - YAMAHA® F150XB

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
1500 rpm	5	9	1	5
2000 rpm	7	10	2	8
2500 rpm	7	12	3	11
3000 rpm	10	16	4	15
3500 rpm	21	33	5	18
4000 rpm	26	41	6	24
4500 rpm	29	47	8	30
5000 rpm	33	53	10	39
5500 rpm	37	59	14	54
WOT	40	64	16	62

FUEL FLOW DATA - 202F - YAMAHA® F200XB

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
1500 rpm	6	10	1	5
2000 rpm	7	12	2	8
2500 rpm	8	13	3	11
3000 rpm	11	18	4	16
3500 rpm	23	37	5	19
4000 rpm	29	46	7	25
4500 rpm	33	53	8	31
5000 rpm	37	59	11	41
5500 rpm	41	66	15	56
WOT	44	71	17	64

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Impeller, Boat Bottom Condition, and Operator Technique.



STANDARDS

HULL AND DECK

- Anchor locker/storage
- Bow and stern Eyes, stainless steel
- Cleats, stainless steel
- Fiberglass floor liner
- Fiberglass stringer system
- Flotation Foam
- Gel scheme, all white
- Horn, stainless steel
- Ladder, boarding, fixed
- Meets applicable USCG & Canadian Regs; NMMA Certified using ABYC STDs.
- Navigation Lights
- Rod holders, gunnel mount
- Rub Rail, w/stainless steel insert
- Thru hull fittings, stainless steel
- Winning Edge Protection Plan

HELM

- 12 volt receptacle
- Cell Phone Holder
- Steering Wheel w/knob, stainless steel
- USB charge port

ENGINE / SYSTEMS / DRIVE

- Battery tray(s)
- Bilge pump, automatic

CONSOLE

- Changing room
- Head floor, fiberglass liner
- Windscreen, console removable

TRAILER

- Wellcraft custom trailer, tandem axle
- Galv/Gatorhyde

COCKPIT

- Assist handles, stainless steel
- Baitwell/live well, 24 gallon w/bluecoat, aquarium style, insulated
- Beverage holder(s), synthetic
- Cockpit Interior, choice of
 - Carbon Fiber, Cognac
 - Neutral w/Black Accent, or Seaside
- Courtesy lights
- Cutting station, aft
- Diamond pattern non-skid
- Leaning post w/backrest, folding
- Rod storage, gunnel
- Seating, aft folding bench
- Seating, forward console
- Self bailing cockpit
- Storage, bow



OPTIONS	
HULL AND DECK Anchor w/rope & chain Gel scheme, solid color hull or two-tone, choice of Crimson Red, Denim Blue, Jet Black, Liquid Blue, Phantom Grey, or Seafoam Green Gel scheme, tri-tone, choice of Black/Atomic, Black/Crimson Red Black/Phantom Grey, Black/White, or White/Black Rod holders, pair, *requires T-top (clamp on) Underwater lights	CONSOLE Head, porta pottie (NA Canada) Head, pump-out
TOW SPORTS Ski tow pylon, removable	T-TOPS T-Top, White Frame w/canvas enclosure
COCKPIT Cockpit Reed Flooring, Ash or Dune Cooler, carry-on, 72qt. Transom cutting board w/tool holders	CANVAS Bimini Top (NA w/T-Top) Console cover Sail Shade w/Carbon Fiber Poles
ENTERTAINMENT Stereo System: AM/FM w/Bluetooth* USB & MP3 port Speakers (2)	TRAILER EZ-loader aluminum, tandem axle w/brakes & spare Spare tire, aluminum or galvanized Trailer delete Wheels, aluminum
HELM Compass GPS plotter w/depth sounder, Garmin 741XS	PACKAGES Bow Seating Package Bow seat cushions Mat Package Bow pads Coaming pads Head door pad Helm footrest mat Offshore Package Logos & Designators, Black Mat Package, Kryptek Offshore Graphics, Black or White Stainless Steel Upgrade Package Grab handles Cleats-pull up Beverage Holders Aft rod/beverage holder combo (2)
ENGINE / SYSTEMS / DRIVE Battery charger Battery charger w/trolling motor pre-wire Battery on/off switch Down rigger pre-wire Hydraulic steering (STD on 150 hp and up) Hydraulic tilt steering (90 & 115 hp only) Raw water wash down Trim tabs w/LED Indicators Trolling motor pre-wire VesselView Mobile, Mercury	



NOTES



222 FISHERMAN



SPECIFICATIONS	US	METRIC
L.O.A	22'	6.71 m
Beam	8' 6"	2.54 m
Fuel Capacity	103 gal	389 L
Draft Up	16"	41 cm
Draft Down	34"	86 cm
Maximum Capacity	2,700 lbs	1,225 kg
Persons Capacity	8	8 CE
Approx. Boat Weight	3,400 lbs	1,542 kg
Approx. Boat & Engine Weight	3,900 lbs	1,769 kg
Max HP	250 hp	187 kw
Deadrise	20°	20°
Bridge Clearance	6' 3"	1.90 m
Bridge Clearance w/T-Top	8' 2"	2.49 m
Keel to Top of T-Top	9' 6"	2.90 m
Keel to Top of Windshield	7' 7"	2.31 m
Trailer Height w/T-Top	11' 0"	3.35 m
Trailer Height w/o T-Top	8' 9"	2.67m

POWER RATINGS & WEIGHTS

Engine Type	Propshaft Power		Boat & Engine Weight	
	HP	KW	LBS	KG
Mercury® 150XL FourStroke	150	112	4120	1870
Mercury® 200XL FourStroke DTS	200	149	4180	1900
Mercury® 250XL Verado	250	187	4310	1950
Yamaha® F150XB	150	112	4140	1880
Yamaha® F200XB	200	149	4140	1880
Yamaha® F250XB	250	187	4220	1910
Yamaha® F250XCA	250	187	4220	1910



222F

PERFORMANCE

Power HP/KW	Propeller (Dia x Pitch)		Type	Top Speed		Cruise Range	
	IN	CM		MPH	KPH	MI	KM
Mercury® 150XL FourStroke	14 1/2 X 17	37 x 43	SST	39-42	63-67	350	560
Mercury® 200XL FourStroke DTS	15 1/2 X 17	39 x 43	SST	43-46	69-74	340	550
Mercury® 250XL Verado	15 1/4 X 19	39 X 48	SST	47-50	76-81	340	550
Yamaha® F150XB	15 1/4 x 15	39 x 38	AL	39-42	63-68	320	520
Yamaha® F200XB	14 1/2 X 15	37 X 38	SST	43-46	69-74	330	530
Yamaha® F250XB	15 1/2 X 16	39 X 41	SST	47-50	76-81	320	520

FUEL FLOW DATA - 222F - MERCURY® 150XL FOURSTROKE

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000rpm	8	13	2	8
2500rpm	9	14	4	15
3000rpm	14	23	5	19
3500rpm	23	45	6	23
4000rpm	28	45	8	30
4500rpm	32	52	10	38
5000rpm	37	60	12	45
WOT	40	64	14	53

FUEL FLOW DATA - 222F - MERCURY® 200XL FOURSTROKE DTS

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000rpm	8	13	2	8
2500rpm	9	14	4	15
3000rpm	14	23	5	19
3500rpm	24	39	6	23
4000rpm	29	47	8	30
4500rpm	33	53	10	38
5000rpm	38	61	12	45
5500rpm	41	66	14	53
6000rpm	44	71	17	64
WOT	46	74	20	76

FUEL FLOW DATA - 222F - MERCURY® 250XL VERADO

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000rpm	7	11	3	11
2500rpm	8	13	4	15
3000rpm	8	13	7	26
3500rpm	10	16	10	38
4000rpm	27	43	10	38
4500rpm	35	56	12	45
5000rpm	39	63	16	60
5500rpm	43	69	18	68
6000rpm	47	76	23	87
WOT	50	81	26	98



FUEL FLOW DATA - 222F - YAMAHA® F150XB				
Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	8	13	2	8
2500 rpm	9	14	4	15
3000 rpm	14	23	5	19
3500 rpm	22	35	5	19
4000 rpm	26	42	6	23
4500 rpm	29	47	8	30
5000 rpm	34	55	10	38
5500 rpm	38	61	13	49
WOT	40	64	16	61

FUEL FLOW DATA - 222F - YAMAHA® F200XB				
Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	8	13	2	8
2500 rpm	9	14	4	15
3000 rpm	14	23	5	19
3500 rpm	24	39	5	19
4000 rpm	29	47	7	26
4500 rpm	32	52	10	38
5000 rpm	38	61	13	49
5500 rpm	43	69	17	64
WOT	45	71	20	76

FUEL FLOW DATA - 222F - YAMAHA® F250XB & XCA				
Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	8	13	4	15
2500 rpm	11	18	6	23
3000 rpm	24	39	7	26
3500 rpm	30	48	9	34
4000 rpm	34	55	12	45
4500 rpm	39	63	15	57
5000 rpm	44	71	19	72
5500 rpm	48	77	22	83
WOT	50	81	24	91

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Impeller, Boat Bottom Condition, and Operator Technique.



STANDARDS

HULL AND DECK

- Anchor locker/storage
- Bow and stern Eyes, stainless steel
- Bow rails, stainless steel
- Cleats, pull-up, stainless steel
- Fiberglass floor liner
- Fiberglass stringer system
- Flotation Foam
- Gel scheme, all white
- Gel scheme, under hardtop color, all white
- Horn, stainless steel
- Ladder, boarding, fixed
- Meets applicable USCG & Canadian Regs; NMMA Certified using ABYC STDs.
- Navigation Lights
- Powdercoat, choice of White or Black
- Rod holders, aft transom mounted
- Rod holders, gunnel mount
- Rub Rail, w/stainless steel insert
- Thru hull fittings, stainless steel
- Transom Lighting, LED
- Winning Edge Protection Plan

COCKPIT

- Assist handles, stainless steel
- Baitwell/live well, 23 gallon w/bluecoat, light & timer
- Beverage holder(s), synthetic
- Bolsters, cockpit
- Cockpit Interior, choice of
 - Carbon Fiber, Cognac,
 - Neutral w/Black Accent, or Seaside
- Cooler, under leaning post (removable)
- Courtesy Lights
- Cutting station, aft
- Diamond pattern non-skid
- Helm seating, leaning post w/backrest, rod holders
- Rod storage, gunnel
- Seating, aft folding bench
- Seating, forward console
- Self bailing cockpit
- Storage, bow
- Transom Door

HELM

- 12 volt receptacle
- Compass
- Steering Wheel w/knob, stainless steel
- USB charge port

ENGINE / SYSTEMS / DRIVE

- Battery on/off switch
- Battery tray(s)
- Bilge pump, automatic
- Hydraulic steering (STD on 150 hp and up)
- Raw water wash down

CONSOLE

- Changing room
- Head floor, fiberglass liner
- Head, porta pottie (NA Canada)
- Rod holders
- Tackle storage curtains
- Windscreen, console, frameless glass



OPTIONS	
HULL AND DECK Anchor w/rope & chain Bow anchor roller Gel scheme, solid color hull or two-tone, choice of Crimson Red, Denim Blue, Jet Black, Liquid Blue, Phantom Grey, or Seafoam Green Gel scheme, tri-tone, choice of Black/Atomic, Black/Crimson Red, Black/Phantom Grey, Black/White, or White/Black Gel scheme, under hardtop color, choice of Crimson Red, Denim Blue, Jet Black, Liquid Blue, Phantom Grey, or Seafoam Green Underwater lights Windlass, w/rope, chain and anchor	CONSOLE Head, electric, porcelain toilet Head, overboard discharge T-TOPS T-Top Deluxe, LED lights, electronics box, spreader lights, rod holders, phone holder & Ski Tow T-Top w/rod holder & Ski Tow, Fiberglass CANVAS Bimini Top (NA w/T-Top) Console & helm seat cover Sail Shade w/Carbon Fiber Poles Spray shields, Eisenglass (T-Top only) TRAILER Wellcraft custom trailer, tandem axle Galv/Gatorhyde EZ-loader aluminum, tandem axle w/brakes & spare Spare tire, aluminum or galvanized Wheels, aluminum PACKAGES Bow Seating Package Bow backrest cushions Bow seat cushions Offshore Package Logos & Designators, Black Mat Package, Kryptek Mat Padding, helm floor & rod storage Offshore Graphics, Black or White Premium Sound Package Fusion stereo JL Audio amplifier JL Audio speakers JL Audio subwoofer(s) Premium Sound Package w/Deluxe T-Top Fusion stereo JL Audio amplifier JL Audio speakers JL Audio subwoofer(s)
COCKPIT Bow fill-in cushion (Req. Bow Seating Pkg.) Cockpit Reed Flooring, Ash or Dune Ladder, retractable (starboard) Macerator, forward floor storage Mat Package, helm floor, rod storage Seating, backrest, forward facing removable Table, bow Transom cutting board w/tool holders	
ENTERTAINMENT Stereo System: AM/FM w/Bluetooth* USB & MP3 port Speakers (2) Stereo System w/Deluxe T-Top: AM/FM w/Bluetooth* USB & MP3 port Speakers (4)	
HELM GPS plotter w/depth sounder, Garmin 7610 XSV VHF radio, Garmin 110	
ENGINE / SYSTEMS / DRIVE Batteries dual w/switch Battery charger Down rigger pre-wire Power assisted steering (select engines only) Tilt steering Trim tabs w/LED Indicators VesselView Mobile, Mercury	



NOTES



242 FISHERMAN



SPECIFICATIONS

	US	METRIC
L.O.A	24' 4"	7.42 m
Beam	8' 6"	2.54 m
Fuel Capacity	158 gal	598 L
Draft Up	16"	40.64 cm
Draft Down	34"	86.36 cm
Maximum Capacity	3,500 lbs	1,588 kg
Persons Capacity	10	10 CE
Approx. Boat Weight	4,050 lbs	1,840 kg
Approx. Boat & Engine Weight	4,900 lbs	2,223 kg
Max HP	400 hp	298 kw
Deadrise	20°	20°
Bridge Clearance	6' 7"	2.01 m
Bridge Clearance w/T-Top	8' 6"	2.59 m
Keel to Top of T-Top	9' 10"	3.00 m
Keel to Top of Windshield	7' 11"	2.41 m
Trailer Height w/T-Top	11' 4"	3.46 m
Trailer Height w/o T-Top	9' 6"	2.90 m

POWER RATINGS & WEIGHTS

Engine Type	Propshaft Power		Boat & Engine Weight	
	HP	KW	LBS	KG
Mercury® 250XXL Verado	250	187	4710	2140
Mercury® 300XXL Verado	300	224	4710	2140
Mercury® 350XXL Verado	350	261	4710	2140
Twin Mercury® 150XL FourStroke	300	224	4990	2260
Twin Mercury® 200XL FourStroke DTS	400	298	5100	2310
Yamaha® F250UCA	250	187	4620	2100
Yamaha® F300UCA	300	224	4620	2100
Twin Yamaha® F150XB	300	224	5030	2280
Twin Yamaha® F200XB & F200XCA	400	298	5030	2280



242F

PERFORMANCE

Power HP/KW	Propeller (Dia x Pitch)		Type	Top Speed		Cruise Range	
	IN	CM		MPH	KPH	MI	KM
Mercury® 250XXL Verado	145/8 X 17	37 X 43	SST	43-46	69-74	270	440
Mercury® 300XXL Verado	145/8 X 17	37 X 43	SST	47-50	76-81	270	440
Mercury® 350XXL Verado	145/8 X 17	37 X 43	SST	50-53	81-85	270	430
Twin Mercury® 150XL FourStroke	14 X 19	36 X 48	SST	49-52	79-84	260	420
Twin Mercury® 200XL FourStroke DTS	143/4 X 21	37 X 53	SST	54-57	87-92	270	430
Yamaha® F250UCA	153/4 X 15	40 X 38	SST	43-46	69-74	260	420
Yamaha® F300UCA	151/2 X 17	39 X 43	SST	47-50	76-81	260	420
Twin Yamaha® F150XB	141/4 X 18	36 X 46	SST	48-51	77-82	250	400
Twin Yamaha® F200XB & F200XCA	141/4 X 18	36 X 46	SST	53-56	85-90	250	400

FUEL FLOW DATA - 242F - MERCURY® 250XXL VERADO

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	8	13	3	11
2500 rpm	9	14	5	19
3000 rpm	11	18	7	26
3500 rpm	16	26	9	34
4000 rpm	28	45	10	38
4500 rpm	33	53	13	49
5000 rpm	36	58	17	64
5500 rpm	39	63	19	72
6000 rpm	42	68	22	83
WOT	44	71	24	91

FUEL FLOW DATA - 242F - MERCURY® 300XXL VERADO

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	8	13	3	11
2500 rpm	9	14	6	23
3000 rpm	11	18	8	30
3500 rpm	15	24	9	34
4000 rpm	30	48	11	42
4500 rpm	36	58	13	49
5000 rpm	39	63	18	68
5500 rpm	43	69	22	83
6000 rpm	45	72	25	95
WOT	48	77	28	106

FUEL FLOW DATA - 242F - MERCURY® 350XXL VERADO

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	8	13	4	15
2500 rpm	9	14	6	23
3000 rpm	11	18	7	26
3500 rpm	16	26	9	34
4000 rpm	32	52	11	42



4500 rpm	38	61	14	53
5000 rpm	42	68	19	72
5500 rpm	46	74	26	98
6000 rpm	49	79	30	113
WOT	52	64	31	117

FUEL FLOW DATA - 242F - TWIN MERCURY®150XL FOURSTROKE

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	9	14	5	19
2500 rpm	10	16	7	26
3000 rpm	21	34	10	38
3500 rpm	29	47	12	45
4000 rpm	34	55	16	60
4500 rpm	40	64	20	76
5000 rpm	44	71	23	87
5500 rpm	48	77	26	98
WOT	49	79	28	106

FUEL FLOW DATA - 242F - TWIN MERCURY®200XL FOURSTROKE DTS

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	9	14	4	15
2500 rpm	10	16	6	23
3000 rpm	22	35	9	34
3500 rpm	29	47	11	42
4000 rpm	36	58	14	53
4500 rpm	41	66	17	64
5000 rpm	46	74	22	83
5500 rpm	50	81	28	106
6000 rpm	54	87	32	121
WOT	57	92	37	140

FUEL FLOW DATA - 242F - YAMAHA® F250UCA

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	8	13	3	11
2500 rpm	9	14	6	23
3000 rpm	10	16	7	26
3500 rpm	14	23	8	30
4000 rpm	29	47	10	38
4500 rpm	33	53	13	49
5000 rpm	37	60	16	60
5500 rpm	40	64	19	72
WOT	44	71	23	87



FUEL FLOW DATA - 242F - YAMAHA® F300UCA

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	8	13	3	11
2500 rpm	9	14	6	23
3000 rpm	10	16	7	26
3500 rpm	14	23	8	30
4000 rpm	30	48	11	42
4500 rpm	35	56	15	57
5000 rpm	39	63	19	72
5500 rpm	43	69	23	87
WOT	47	76	27	102

FUEL FLOW DATA - 242F - TWIN YAMAHA®F150XB

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	9	14	5	19
2500 rpm	10	16	6	23
3000 rpm	21	34	7	26
3500 rpm	28	45	9	34
4000 rpm	33	53	10	38
4500 rpm	38	61	13	49
5000 rpm	42	68	18	68
5500 rpm	46	74	26	98
WOT	49	79	28	106

FUEL FLOW DATA - 242F - TWIN YAMAHA® F200XB & F200XCA

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	9	14	5	19
2500 rpm	10	16	8	30
3000 rpm	23	37	8	30
3500 rpm	31	50	11	42
4000 rpm	38	61	15	57
4500 rpm	43	69	18	68
5000 rpm	48	77	24	91
5500 rpm	52	84	34	129
WOT	56	90	37	140

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Impeller, Boat Bottom Condition, and Operator Technique.



STANDARDS

HULL AND DECK

Anchor locker/storage
Bow and stern Eyes, stainless steel
Bow rails, stainless steel
Cleats, pull-up, stainless steel
Fiberglass floor liner
Fiberglass stringer system
Flotation Foam
Gel scheme, all white
Gel scheme, under hardtop color, all white
Horn, stainless steel
Ladder, boarding, fixed
Meets applicable USCG & Canadian Regs;
NMMA Certified using ABYC STDs.
Navigation Lights
Powdercoat, choice of White or Black
Rod holders, aft transom mounted
Rod holders, gunnel mount
Rub Rail, w/stainless steel insert
Thru hull fittings, stainless steel
Transom Lighting, LED
Winning Edge Protection Plan

COCKPIT

5 gallon bucket in holder
Assist handles, stainless steel
Baitwell/live well, 23 gallon w/bluecoat,
light & timer
Baitwell/live well, 17 gallon w/bluecoat,
light & timer
Beverage holder(s), synthetic
Bolsters, cockpit
Cockpit Interior, choice of
Carbon Fiber, Cognac,
Neutral w/Black Accent, or Seaside
Cooler, under leaning post (removable)
Courtesy Lights
Cutting station, aft
Diamond pattern non-skid
Helm seating, leaning post w/backrest,
rod holders
Rod storage, gunnel
Seating, aft folding bench
Seating, forward console
Self bailing cockpit
Storage, bow
Tackle storage w/boxes
Transom Door

HELM

12 volt receptacle
Compass
Steering Wheel w/knob, stainless steel
USB charge port

ENGINE / SYSTEMS / DRIVE

Battery on/off switch
Battery tray(s)
Bilge pump, automatic
Hydraulic steering (STD on 150 hp and up)
Raw water wash down
Trim tabs w/LED Indicators

CONSOLE

Changing room
Head floor, fiberglass liner
Head, porta pottie (NA Canada)
Rod holders
Tackle storage curtains
Windscreen, console,
frameless glass



OPTIONS

HULL AND DECK

Anchor w/rope & chain
Bow anchor roller
Gel scheme, solid color hull or two-tone,
choice of Crimson Red, Denim Blue,
Jet Black, Liquid Blue, Phantom Grey,
or Seafoam Green
Gel scheme, tri-tone, choice of
Black/Atomic, Black/Crimson Red,
Black/Phantom Grey, Black/White,
or White/Black
Gel scheme, under hardtop color, choice
of Crimson Red, Denim Blue, Jet Black
Liquid Blue, Phantom Grey,
or Seafoam Green
Underwater lights
Windlass, w/rope, chain and anchor

COCKPIT

Bow fill-in cushion
(Req. Bow Seating Pkg.)
Cockpit Reed Flooring, Ash or Dune
Cockpit Sink w/transom shower,
fresh water
Helm seating upgrade, w/baitwell
& cutting board
Ladder, retractable (starboard)
Macerator, forward floor storage
Mat Package, helm floor, rod storage
Seating, backrest, forward facing
removable
Table, bow
Transom cutting board w/tool holders

ENTERTAINMENT

Stereo System:
AM/FM w/Bluetooth*
USB & MP3 port
Speakers (2)
Stereo System w/Deluxe T-Top:
AM/FM w/Bluetooth
USB & MP3 port
Speakers (4)

HELM

GPS plotter w/depth sounder, Garmin
7610 XSV
VHF radio, Garmin 110

ENGINE / SYSTEMS / DRIVE

Batteries dual w/switch
Battery charger
Down rigger pre-wire
Power assisted steering
(select engines only)
Tilt steering
VesselView Mobile, Mercury

CONSOLE

Head, electric, porcelain toilet
Head, overboard discharge

T-TOPS

T-Top Deluxe, LED lights, electronics box,
spreader lights, rod holders, phone
holder & Ski Tow
T-Top w/rod holder & Ski Tow, Fiberglass

CANVAS

Bimini Top (NA w/T-Top)
Console & helm seat cover
Sail Shade w/Carbon Fiber Poles
Spray shields, Eisenglass (T-Top only)

TRAILER

Wellcraft custom trailer, tandem axle
Galv/Gatorhdye
EZ-loader aluminum, tandem axle w/
brakes & spare
Spare tire, aluminum or galvanized
Wheels, aluminum

PACKAGES

Bow Seating Package

Bow backrest cushions
Bow seat cushions

Offshore Package

Logos & Designators, Black
Mat Package, Kryptek
Mat Padding, helm floor & rod storage
Offshore Graphics, Black or White

Premium Sound Package

Fusion stereo
JL Audio amplifier
JL Audio speakers
JL Audio subwoofer(s)

Premium Sound Package w/Deluxe T-Top

Fusion stereo
JL Audio amplifier
JL Audio speakers
JL Audio subwoofer(s)



262 FISHERMAN



SPECIFICATIONS

	US	METRIC
LOA	26' 4"	8.02 m
Beam	9'0"	2.74 m
Fuel Capacity	158 gal	598 L
Draft Up	20"	51 cm
Draft Down	29"	74 cm
Maximum Capacity	Yacht	1,700 kg
Persons Capacity	Yacht	10 CE
Approx. Boat Weight	5,550 lbs	2,520 kg
Approx. Boat & Engine Weight	6,800 lbs	3,084 kg
Max HP	500 hp	373 kw
Deadrise	21°	21°
Bridge Clearance w/T-Top	8' 8"	2.64 m
Keel to Top of T-Top	10' 2"	3.10 m
Keel to Top of Windshield	8' 2"	2.49 m
Trailer Height w/T-Top	11' 9"	3.58 m
Trailer Height w/o T-Top	9' 10"	3.00 m

POWER RATINGS & WEIGHTS

Engine Type	Propshaft Power		Boat & Engine Weight	
	HP	KW	LBS	KG
Mercury® 300XXL Verado	300	224	6360	2890
Mercury® 350XXL Verado	350	261	6360	2890
Twin Mercury® 150XL FourStroke	300	224	6640	3010
Twin Mercury® 200XL FourStroke DTS	400	298	6740	3060
Twin Mercury® 250XL Verado	500	373	7020	3180
Yamaha® F300UCA	300	224	6280	2860
Yamaha® F350UCC	350	261	6480	2940
Twin Yamaha® F150XB	300	224	6680	3030
Twin Yamaha® F200XB & F200XCA	400	298	6680	3030
Twin Yamaha® F250XCA	500	373	6840	3100



262F

PERFORMANCE

Power HP/ KW	Propeller (Dia x Pitch)		Type	Top Speed		Cruise Range	
	IN	CM		MPH	KPH	MI	KM
Mercury® 300XXL Verado	14 5/8 X 17	37 X 43	SST	42-45	68-72	300	485
Mercury® 350XXL Verado	14 5/8 X 17	37 X 43	SST	45-48	72-77	300	485
Twin Mercury® 150XL FourStroke	14 X 19	36 X 48	SST	44-47	71-76	280	450
Twin Mercury® 200XL FourStroke DTS	14 3/4 X 21	37 X 53	SST	52-55	84-89	280	450
Twin Mercury® 250XL Verado	14 3/4 X 21	37 X 53	SST	57-60	92-97	270	435
Yamaha® F300UCA	15 3/4 X 15	40 X 38	SST	42-45	68-72	300	485
Yamaha® F350UCC	16 1/4 X 17	41 X 43	SST	45-48	72-77	285	460
Twin Yamaha® F150XB	14 1/4 X 17	36 X 43	SST	44-47	71-76	270	435
Twin Yamaha® F200XB & F200XCA	14 1/4 X 17	36 X 43	SST	52-55	84-89	260	420
Twin Yamaha® F250XCA	15 X 21	38 X 53	SST	57-60	92-97	270	435

FUEL FLOW DATA - 262F - MERCURY® 300XXL VERADO

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	9	14	3	11
2500 rpm	9	14	5	19
3000 rpm	10	16	7	26
3500 rpm	13	21	9	34
4000 rpm	26	42	12	45
4500 rpm	31	50	15	57
5000 rpm	34	55	18	68
5500 rpm	38	61	20	76
6000 rpm	41	66	23	87
WOT	44	71	26	98

FUEL FLOW DATA - 262F - MERCURY® 350XXL VERADO

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	9	14	3	11
2500 rpm	9	14	5	19
3000 rpm	10	16	7	26
3500 rpm	14	23	10	38
4000 rpm	27	43	14	53
4500 rpm	33	53	17	64
5000 rpm	36	58	21	79
5500 rpm	41	66	24	91
6000 rpm	44	71	27	102
WOT	47	76	31	117

FUEL FLOW DATA - 262F - TWIN MERCURY® 150XL FOURSTROKE

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	9	14	5	19
2500 rpm	10	16	6	23
3000 rpm	21	34	7	26
3500 rpm	27	43	9	34
4000 rpm	32	52	10	38



4500 rpm	36	58	13	49
5000 rpm	40	64	18	68
5500 rpm	44	71	25	95
WOT	46	74	28	106

FUEL FLOW DATA - 262F - TWIN MERCURY®200XL FOURSTROKE DTS

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	9	14	5	19
2500 rpm	10	16	7	26
3000 rpm	13	21	9	34
3500 rpm	33	53	14	53
4000 rpm	36	58	15	57
4500 rpm	43	69	18	68
5000 rpm	47	76	24	91
5500 rpm	50	81	31	117
6000 rpm	52	84	34	129
WOT	54	87	39	147

FUEL FLOW DATA - 262F - TWIN MERCURY®250XL VERADO

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	9	14	6	23
2500 rpm	10	16	11	42
3000 rpm	13	21	16	60
3500 rpm	34	55	18	68
4000 rpm	38	61	23	87
4500 rpm	45	72	29	109
5000 rpm	50	81	37	140
5500 rpm	54	87	44	166
6000 rpm	57	92	49	185
WOT	59	95	52	197

FUEL FLOW DATA - 262F - YAMAHA® F300UCA

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	9	14	3	11
2500 rpm	9	14	5	19
3000 rpm	10	16	7	26
3500 rpm	13	21	9	34
4000 rpm	28	45	12	45
4500 rpm	33	53	15	57
5000 rpm	36	58	18	68
5500 rpm	40	64	22	83
WOT	44	71	25	95



FUEL FLOW DATA - 262F - YAMAHA® F350UCC

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	9	14	5	20
2500 rpm	10	16	7	28
3000 rpm	11	17	10	36
3500 rpm	13	21	11	43
4000 rpm	30	48	15	56
4500 rpm	35	56	18	68
5000 rpm	39	62	22	84
5500 rpm	43	69	27	103
WOT	46	74	34	127

FUEL FLOW DATA - 262F - TWIN YAMAHA®F150XB

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	9	14	5	19
2500 rpm	10	16	6	23
3000 rpm	21	34	7	26
3500 rpm	27	43	9	34
4000 rpm	32	52	10	38
4500 rpm	36	58	13	49
5000 rpm	40	64	18	68
5500 rpm	43	69	25	95
WOT	46	74	28	106

FUEL FLOW DATA - 262F - TWIN YAMAHA® F200XB & F200XCA

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	9	14	5	19
2500 rpm	10	16	8	30
3000 rpm	23	37	8	30
3500 rpm	30	48	11	42
4000 rpm	37	60	15	57
4500 rpm	41	67	18	68
5000 rpm	46	74	25	95
5500 rpm	49	79	34	129
WOT	53	85	37	140



FUEL FLOW DATA - 262F - TWIN YAMAHA® F250XCA				
Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	9	14	7	26
2500 rpm	10	16	10	38
3000 rpm	14	23	12	45
3500 rpm	33	53	17	64
4000 rpm	40	64	22	83
4500 rpm	46	74	27	102
5000 rpm	52	84	34	128
5500 rpm	56	90	42	159
WOT	59	95	50	183

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Impeller, Boat Bottom Condition, and Operator Technique.



STANDARDS

HULL AND DECK

- Anchor locker/storage
- Anchor rod tie off
- Bow anchor roller
- Bow and stern Eyes, stainless steel
- Bow rails, stainless steel
- Bronze underwater fittings
- Cleats, pull-up, stainless steel
- Fiberglass floor liner
- Fiberglass stringer system
- Flotation Foam
- Gel scheme, all white
- Gel scheme, under hardtop color, all white
- Horn, stainless steel
- Ladder, boarding, fixed
- Meets applicable USCG & Canadian Regs; NMMA Certified using ABYC STDs.
- Navigation Lights
- Powdercoat, choice of White or Black
- Rod holders, aft transom mounted
- Rod holders, gunnel mount
- Rub Rail, w/stainless steel insert
- Thru hull fittings, stainless steel
- Transom Lighting, LED
- Winning Edge Protection Plan

COCKPIT

- 5 gallon bucket in holder
- Assist handles, stainless steel
- Baitwell/live well, 23 gallon w/bluecoat, light & timer
- Baitwell/live well, 17 gallon w/bluecoat, light & timer
- Beverage holder(s), synthetic
- Bolsters, cockpit
- Cockpit Interior, choice of
 - Carbon Fiber, Cognac,
 - Neutral w/Black Accent, or Seaside
- Cooler, removable
- Cooler, under leaning post (removable)
- Cutting station, aft
- Diamond pattern non-skid
- Helm seating, leaning post w/backrest, rod holders
- Rod storage, gunnel
- Seating, aft folding bench
- Seating, forward console
- Self bailing cockpit
- Storage, bow
- Storage/Fishbox(es) w/macerator and overboard drain
- Tackle storage w/boxes
- Transom Door

ENTERTAINMENT

- Stereo System:
 - AM/FM w/Bluetooth*
 - USB & MP3 port
- Speakers (2)

HELM

- 12 volt receptacle
- Compass
- Steering Wheel w/knob, stainless steel
- USB charge port

ENGINE / SYSTEMS / DRIVE

- Batteries dual w/switch
- Battery on/off switch
- Battery tray(s)
- Bilge pump, automatic
- Hydraulic steering (STD on 150 hp and up)
- Raw water wash down
- Tilt steering
- Trim tabs w/LED Indicators

CONSOLE

- Changing room
- Head floor, fiberglass liner
- Head, lighting
- Head, porta pottie (NA Canada)
- Tackle storage curtains
- Windscreen, console
- frameless glass

T-TOPS

- T-Top w/rod holder & ski tow, fiberglass



OPTIONS	
HULL AND DECK Anchor w/rope & chain Dive door Gel scheme, solid color hull or two-tone, choice of Crimson Red, Denim Blue, Jet Black, Liquid Blue, Phantom Grey, or Seafoam Green Gel scheme, tri-tone, choice of Black/Atomic, Black/Crimson Red, Black/Phantom Grey, Black/White, or White/Black Gel scheme, under hardtop color, choice of Crimson Red, Denim Blue, Jet Black Liquid Blue, Phantom Grey, or Seafoam Green Underwater lights Windlass, w/rope, chain and anchor	CONSOLE Head, electric, porcelain toilet Head, overboard discharge T-TOPS T-Top Deluxe, LED lights, electronics box, spreader lights, rod holders, & phone holder CANVAS Console & helm seat cover Sail Shade w/Carbon Fiber Poles Spray shields, Eisenglass (T-Top only) TRAILER EZ-loader aluminum, triple axle w/brakes & spare PACKAGES Bow Seating Package Bow backrest cushions Bow seat cushions Offshore Package Logos & Designators, Black Mat Package, Kryptek Mat Padding, helm floor & rod storage Offshore Graphics, Black or White Premium Sound Package Fusion stereo JL Audio amplifier JL Audio speakers JL Audio subwoofer(s) Premium Sound Package w/Deluxe T-Top Fusion stereo JL Audio amplifier JL Audio speakers JL Audio subwoofer(s)
COCKPIT Bow fill-in cushion (Req. Bow Seating Pkg.) Cockpit Reed Flooring, Ash or Dune Cockpit Sink w/transom shower, fresh water Helm seating upgrade, w/baitwell & cutting board Ladder, retractable (starboard) Mat Package, helm floor, rod storage Mat Package, helm floor, rod storage, leaning post and baitwell mats Seating, backrest, forward facing removable Storage trays, aft, tilt out Storage trays, forward, port & stbd, tilt out Storage trays, tilt out w/dive door Table, bow Transom cutting board w/tool holders	
HELM GPS plotter w/depth sounder, Garmin 7610 XSV Night Vision, FLIR VHF radio, Garmin 110	
ENGINE / SYSTEMS / DRIVE Battery charger Down rigger pre-wire Power assisted steering (select engines only) VesselView Mobile, Mercury	



NOTES



302 FISHERMAN



SPECIFICATIONS

	US	METRIC
L.O.A	30' 2"	9.20 m
Beam	9' 8"	2.95 m
Fuel Capacity	268 gal	1010 L
Draft Up	23"	58 cm
Draft Down	31"	78 cm
Maximum Capacity	Yacht	1,850 kg
Persons Capacity	Yacht	12 CE
Approx. Boat Weight	7,800 lbs	3,538 kg
Approx. Boat & Engine Weight	9,200 lbs	4,173 kg
Water Capacity	13 gal	49 L
Max HP	800 hp	596 kw
Deadrise	22°	22°
Bridge Clearance w/T-top	8' 2"	2.49 m
Keel to Top of T-Top	10' 0"	3.05 m
Keel to Top of Windshield	8' 8"	2.64 m
Trailer Height w/T-Top	11' 11"	3.63 m

POWER RATINGS & WEIGHTS

Engine Type	Propshaft Power		Boat & Engine Weight	
	HP	KW	LBS	KG
Twin Mercury 250XL Verado	500	373	7399	3356
Twin Mercury 300XL Verado & JPO	600	447	7399	3356
Twin Mercury 350XL Verado & JPO	700	522	7435	3372
Twin Mercury 400RXL Verado & JPO	800	596	7435	3372
Twin Yamaha F250XCA & Helm Master	500	373	7318	3319
Twin Yamaha F300XCA & Helm Master	600	447	7318	3319

**302F**

PERFORMANCE

Power HP/ KW	Propeller (Dia x Pitch)		Type	Top Speed		Cruise Range	
	IN	CM		MPH	KPH	MI	KM
Twin Mercury 250XL Verado	14 5/8 x 17	37 x 43	SST	49-53	79-85	330	530
Twin Mercury 300XL Verado & JPO	14 5/8 x 19	37 x 48	SST	52-56	84-90	320	510
Twin Mercury 350XL Verado & JPO	14 5/8 x 19	37 x 48	SST	56-59	90-95	310	500
Twin Mercury 400RXL Verado & JPO	14 5/8 x 17	37 x 43	SST	59-62	95-100	272	437
Twin Yamaha F250XCA & Helm Master	15 1/2 x 17	39 x 43	SST	49-53	79-85	373	600
Twin Yamaha F300XCA & Helm Master	15 1/4 x 18	39 x 46	SST	52-56	84-90	372	599

FUEL FLOW DATA - 302F - TWIN MERCURY 250XL VERADO

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	8	13	6	22
2500 rpm	8	13	9	33
3000 rpm	9	14	13	47
3500 rpm	13	20	16	62
4000 rpm	29	47	21	81
4500 rpm	38	60	27	103
5000 rpm	43	69	34	127
5500 rpm	46	75	41	156
6000 rpm	49	78	48	181
WOT	50	80	50	189

FUEL FLOW DATA - 302F - TWIN MERCURY 300XL VERADO & JPO

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	8	14	7	25
2500 rpm	9	14	10	37
3000 rpm	9	15	14	53
3500 rpm	14	22	18	70
4000 rpm	31	50	24	90
4500 rpm	40	65	30	115
5000 rpm	46	74	38	142
5500 rpm	50	80	46	175
6000 rpm	52	84	53	202
WOT	53	86	56	212

FUEL FLOW DATA - 302F - TWIN MERCURY 350XL VERADO & JPO

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	9	14	7	28
2500 rpm	9	15	11	41
3000 rpm	10	16	16	59
3500 rpm	14	23	20	77
4000 rpm	33	54	26	100



4500 rpm	43	69	34	127
5000 rpm	49	79	42	157
5500 rpm	53	85	51	193
6000 rpm	56	90	59	223
WOT	57	91	62	234

FUEL FLOW DATA - 302F - TWIN MERCURY 400RXL VERADO & JPO

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2500 rpm	10	16	10	37
3000 rpm	10	16	15	56
3500 rpm	12	19	20	75
4000 rpm	18	28	26	98
4500 rpm	37	60	33	124
5000 rpm	46	74	41	156
5500 rpm	53	85	51	193
6000 rpm	57	92	62	235
6500 rpm	60	96	71	267
WOT	61	98	76	288

FUEL FLOW DATA - 302F - TWIN YAMAHA F250XCA & HELM MASTER

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	9	14	7	25
2500 rpm	10	16	10	38
3000 rpm	15	23	13	50
3500 rpm	28	44	16	61
4000 rpm	33	53	21	78
4500 rpm	37	60	27	101
5000 rpm	42	67	33	124
5500 rpm	46	74	38	146
WOT	49	79	47	178

FUEL FLOW DATA - 302F - TWIN YAMAHA F300XCA & HELM MASTER

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	9	15	7	27
2500 rpm	11	17	11	41
3000 rpm	15	24	14	54
3500 rpm	29	47	17	65
4000 rpm	34	55	22	84
4500 rpm	39	63	29	109
5000 rpm	44	71	35	133
5500 rpm	48	78	42	157
WOT	51	83	51	192

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Impeller, Boat Bottom Condition, and Operator Technique.



STANDARDS

HULL AND DECK

Anchor locker/storage
Anchor rod tie off
Bow anchor roller
Bow and stern Eyes, stainless steel
Bow rails, stainless steel
Bronze underwater fittings
Cleats, pull-up, stainless steel
Fiberglass floor liner
Fiberglass stringer system
Flotation Foam
Gel scheme, all white
Gel scheme, under hardtop color, all white
Horn, stainless steel
Ladder, boarding, retractable
Meets applicable USCG & Canadian Regs;
NMMA Certified using ABYC STDs.
Navigation Lights
Powdercoat, choice of White or Black
Rod holders, aft transom mounted
Rod holders, gunnel mount
Rub Rail, w/stainless steel insert
Thru hull fittings, stainless steel
Transom Lighting, LED
Winning Edge Protection Plan

COCKPIT

5 gallon bucket in holder, 2
Assist handles, powdercoat
Baitwell/live well, 23 gallon w/bluecoat,
light & timer, 2
Beverage holder(s), SST
Bolsters, cockpit
Cockpit Interior, choice of
Carbon Fiber, Cognac,
Neutral w/Black Accent, or Seaside
Cockpit Sink w/transom shower,
fresh water
Cutting station, aft
Deck lids w/stainless steel latches
Rod storage, gunnel
Diamond pattern non-skid
Helm seating, dual captain chair
Rod storage, gunnel
Seating, aft folding bench
Seating, forward console
Self bailing cockpit
Storage, bow
Storage/Fishbox w/overboard drain
Storage/Fishbox(es) w/macerator and
overboard drain
Tackle storage w/boxes
Transom cutting board w/tool holders

ENTERTAINMENT

Stereo System w/Deluxe T-Top:
AM/FM w/Bluetooth
USB & MP3 port
Speakers (4)

HELM

12 volt receptacle
Cell phone holder
Compass
Steering Wheel w/knob, stainless steel
USB charge port, 2

ENGINE / SYSTEMS / DRIVE

Batteries dual w/switch
Battery on/off switch
Battery tray(s)
Bilge pump, automatic
Freshwater system
Hydraulic steering (STD on 150 hp and up)
Raw water wash down
Tilt steering
Trim tabs w/LED Indicators

CONSOLE

Changing room
Counter top, corian
Head floor, fiberglass liner
Head, electric, porcelain toilet
Head, lighting
Head, mirror
Port light window, opening
Sink w/faucet
Sky light
Tackle storage curtains
Windscreen, console
frameless glass
Windshield, Deluxe w/side entry

T-TOPS

T-Top Deluxe w/Ladder back, LED lights,
electronics box, spreader lights,
& rod holders



OPTIONS	
HULL AND DECK Anchor w/rope & chain Dive door Gel scheme, solid color hull or two-tone, choice of Crimson Red, Denim Blue, Jet Black, Liquid Blue, Phantom Grey, or Seafoam Green Gel scheme, tri-tone, choice of Black/Atomic, Black/Crimson Red, Black/Phantom Grey, Black/White, or White/Black Gel scheme, under hardtop color, choice of Crimson Red, Denim Blue, Jet Black, Liquid Blue, Phantom Grey, or Seafoam Green Ladder, dive door Underwater lights Windlass, w/rope, chain and anchor	CONSOLE Head, overboard discharge Head, wood floor T-TOPS Outriggers, Taco grand slam CANVAS Console & helm seat cover Sail Shade w/Carbon Fiber Poles Spray shields, Eisenglass (T-Top only) TRAILER EZ-loader aluminum, triple axle w/brakes & spare PACKAGES Bow Seating Package Bow backrest cushions Bow seat cushions Offshore Package Logos & Designators, Black Mat Package, Kryptek Mat Padding, helm floor & rod storage Offshore Graphics, Black or White Premium Sound Package w/Deluxe T-Top Fusion stereo JL Audio amplifier JL Audio speakers JL Audio subwoofer(s)
COCKPIT Bow fill-in cushion (Req. bow cooler & table) Cockpit Reed Flooring, Ash or Dune Cooler, bow Grill, cockpit (Req. dockside power) Mat Package, helm floor, rod storage Seating, backrest, forward facing removable Seating, forward lounge, convertible Storage trays, aft, tilt out Storage trays, tilt out w/dive door Table, bow Transom seat, delete	
HELM GPS plotter w/depth sounder, Garmin 7616XSV MFD w/ 1KW Transducer Night Vision, FLIR Radar, 4KW Open Array Satellite Weather (Req. GPS) Transducer, 1KW VHF radio, Garmin 110	
ENGINE / SYSTEMS / DRIVE Active Trim (Mercury Only) Battery charger Dockside power Down rigger pre-wire Power assisted steering (select engines only) VesselView Mobile, Mercury	



NOTES



352 FISHERMAN



SPECIFICATIONS

	US	METRIC
L.O.A	35' 6"	10.76 m
Beam	10' 8"	3.25 m
Fuel Capacity	376 gal	1,423 L
Draft Up	26"	66.4 cm
Draft Down	40"	101.4 cm
Maximum Capacity	Yacht	2,350 kg
Persons Capacity	Yacht	14 CE
Approx. Boat Weight	11,500 lbs	5,215 kg
Approx. Boat & Engine Weight	13,510 lbs	6,130 kg
Water Capacity	12 gal	45 L
Max HP	1275 hp	950 kw
Deadrise	23°	23°
Bridge Clearance	9' 4"	2.74 m
Bridge Clearance w/Second Station	15' 10"	4.57 m
Keel to Top of T-Top	10' 5"	3.15 m
Keel to Top of Windshield	9' 6"	2.87 m

POWER RATINGS & WEIGHTS

Engine Type	Propshaft Power		Boat & Engine Weight	
	HP	KW	LBS	KG
Twin Mercury 350XL Verado & JPO	700	522	12,840	5,825
Twin Mercury 400RXL Verado & JPO	800	597	12,840	5,825
Triple Mercury 300XL Verado & JPO	900	671	13,360	6,060
Triple Mercury 350XL Verado & JPO	1,050	783	13,510	6,130
Triple Mercury 400RXL Verado & JPO	1,200	895	13,510	6,130
Twin Yamaha F350XCC & Helm Master	700	522	13,030	5,910
Twin Yamaha XF425XSA & Helm Master	850	633	13,410	6,085
Triple Yamaha F300XCA & Helm Master	900	671	13,190	5,985
Triple Yamaha F350XCC & Helm Master	1,050	783	13,790	6,255
Triple Yamaha XF425XSA & Helm Master	1,275	951	14,360	6,515



352F

PERFORMANCE

Power HP/ KW	Propeller (Dia x Pitch)		Type	Top Speed		Cruise Range	
	IN	CM		MPH	KPH	MI	KM
Twin Mercury 350XL Verado & JPO	145/8 x 15	37 X 38	SST	43-46	63-67	440	708
Twin Mercury 400RXL Verado & JPO	145/8 x 15	37 X 38	SST	46-49	67-72	440	708
Triple Mercury 300XL Verado & JPO	145/8 x 18	37 X 46	SST	50-53	73-78	455	732
Triple Mercury 350XL Verado & JPO	145/8 x 18	37 X 46	SST	56-59	82-87	430	692
Triple Mercury 400RXL Verado & JPO	145/8 x 18	37 X 46	SST	62-65	91-95	440	708
Twin Yamaha F350XCC & Helm Master	161/4 X 15	41 X 38	SST	42-45	62-66	425	684
Twin Yamaha XF425XSA & Helm Master	167/8 X 17	43 X 43	SST	50-53	73-78	450	724
Triple Yamaha F300XCA & Helm Master	151/4 X 18	39 X 46	SST	50-53	73-78	450	724
Triple Yamaha F350XCC & Helm Master	151/2 X 19	39 X 48	SST	55-58	81-85	390	628
Triple Yamaha XF425XSA & Helm Master	161/8 X 23	41 X 58	SST	63-66	92-97	400	644

FUEL FLOW DATA - 352F - TWIN MERCURY 350XL VERADO & JPO

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	8	13	7	28
2500 rpm	12	20	9	36
3000 rpm	17	27	12	47
3500 rpm	24	39	17	62
4000 rpm	29	47	21	78
4500 rpm	34	54	26	96
5000 rpm	37	60	32	120
5500 rpm	40	65	41	155
6000 rpm	43	69	54	204
WOT	45	72	61	231

FUEL FLOW DATA - 352F - TWIN MERCURY 400RXL VERADO & JPO

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2500 rpm	9	14	8	30
3000 rpm	13	22	10	38
3500 rpm	18	29	13	50
4000 rpm	26	42	18	67
4500 rpm	31	50	22	84
5000 rpm	36	58	27	103
5500 rpm	40	64	34	129
6000 rpm	44	70	41	155
6500 rpm	46	74	54	204
WOT	48	77	66	248

FUEL FLOW DATA - 352F - TRIPLE MERCURY 300XL VERADO & JPO

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
1500 rpm	10	15	9	34
2000 rpm	15	23	12	44
2500 rpm	20	31	15	58
3000 rpm	28	46	20	77
3500 rpm	34	54	25	96



4000 rpm	39	63	31	119
4500 rpm	43	70	39	148
5000 rpm	47	76	50	190
5500 rpm	50	80	68	256
WOT	52	84	75	284

FUEL FLOW DATA - 352F - TRIPLE MERCURY 350XL VERADO & JPO

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	11	17	11	41
2500 rpm	16	26	14	53
3000 rpm	22	35	19	70
3500 rpm	32	51	25	93
4000 rpm	38	61	31	117
4500 rpm	44	70	38	145
5000 rpm	48	78	48	180
5500 rpm	53	85	61	232
6000 rpm	56	90	82	312
WOT	58	93	92	346

FUEL FLOW DATA - 352F - TRIPLE MERCURY 400RXL VERADO & JPO

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2500 rpm	12	19	12	44
3000 rpm	18	29	15	57
3500 rpm	24	39	20	75
4000 rpm	35	56	27	100
4500 rpm	42	67	33	126
5000 rpm	48	77	41	155
5500 rpm	53	86	51	193
6000 rpm	58	93	63	239
6500 rpm	61	99	89	338
WOT	64	103	98	372

FUEL FLOW DATA - 352F - TWIN YAMAHA F350XCC & HELM MASTER

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	12	20	10	39
2500 rpm	17	27	14	52
3000 rpm	24	39	18	69
3500 rpm	29	46	23	86
4000 rpm	33	53	28	107
4500 rpm	37	59	35	133
5000 rpm	40	64	44	167
5500 rpm	42	68	60	226
WOT	44	71	67	255



FUEL FLOW DATA - 352F - TWIN YAMAHA XF425XSA & HELM MASTER

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	14	23	11	43
2500 rpm	19	31	15	57
3000 rpm	28	45	20	76
3500 rpm	34	54	25	95
4000 rpm	39	62	31	117
4500 rpm	43	69	39	146
5000 rpm	47	75	49	186
5500 rpm	50	80	66	250
WOT	52	83	74	280

FUEL FLOW DATA - 352F - TRIPLE YAMAHA F300XCA & HELM MASTER

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	15	23	12	45
2500 rpm	20	31	16	59
3000 rpm	28	46	21	79
3500 rpm	34	54	26	99
4000 rpm	39	63	32	122
4500 rpm	43	70	40	152
5000 rpm	47	76	51	192
5500 rpm	50	80	69	259
WOT	52	84	77	293

FUEL FLOW DATA - 352F - TRIPLE YAMAHA F350XCC & HELM MASTER

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	16	26	16	59
2500 rpm	21	34	21	78
3000 rpm	31	50	27	103
3500 rpm	37	60	34	129
4000 rpm	43	69	42	160
4500 rpm	48	76	53	199
5000 rpm	52	83	67	254
5500 rpm	55	88	90	341
WOT	57	92	101	383



FUEL FLOW DATA - 352F - TRIPLE YAMAHA XF425XSA & HELM MASTER				
Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	18	29	17	65
2500 rpm	24	39	23	86
3000 rpm	36	57	30	113
3500 rpm	42	68	38	142
4000 rpm	49	79	46	175
4500 rpm	54	87	58	219
5000 rpm	59	95	74	279
5500 rpm	63	101	99	375
WOT	65	105	111	420

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Impeller, Boat Bottom Condition, and Operator Technique.



STANDARDS

HULL AND DECK

Anchor locker/storage
Anchor rod tie off
Bow anchor roller
Bow and stern Eyes, stainless steel
Bronze underwater fittings
Cleats, pull-up, stainless steel
Dive door
Fiberglass floor liner
Fiberglass stringer system
Flotation Foam
Gel scheme, all white
Gel scheme, under hardtop color, all white
Horn, stainless steel
Ladder, boarding, retractable
Meets applicable USCG & Canadian Regs;
NMMA Certified using ABYC STDs.
Navigation Lights
Powdercoat, choice of White or Black
Rod holders, aft transom mounted
Rod holders, gunnel mount
Rub Rail, w/stainless steel insert
Thru hull fittings, stainless steel
Transom Lighting, LED
Windlass, w/rope, chain and anchor
Winning Edge Protection Plan

COCKPIT

5 gallon bucket in holder, 2
Assist handles, powdercoat
Baitwell/live well, 32 gallon w/bluecoat,
aquarium style, light & timer
Beverage holder(s), SST
Cockpit Interior, choice of
Carbon Fiber, Cognac,
Neutral w/ Black Accent, or Seaside
Cockpit Sink w/transom shower,
fresh water
Cooler, aft, macerated
Cooler, bow
Cutting station, aft
Deck lids w/stainless steel latches
Diamond pattern non-skid
Helm seating, triple captain chair
w/drop down
Non-skid, mechanical pattern
Pails, 2
Rod storage, gunnel
Seating, aft folding bench
Seating, forward console
Self bailing cockpit
Storage, bow
Storage/Fishbox(es) w/macerator
and overboard drain
Storage/Fishbox, transom, 32 gallon
Tackle storage w/boxes
Transom cutting board w/tool holders
Transom Door

CABIN

Seat, step, & storage box (Bamboo
varnish)
Sleeping Accomodations

ENTERTAINMENT

Stereo System w/Deluxe T-Top:
AM/FM w/Bluetooth
USB & MP3 port
Speakers (4)

HELM

12 volt receptacle
Cell phone holder
Compass
Steering Wheel w/knob, stainless steel
USB charge port, 2

ENGINE / SYSTEMS / DRIVE

Batteries dual w/switch
Battery charger
Battery on/off switch
Battery tray(s)
Bilge pump, automatic
Detector, carbon monoxide
Dockside power
Down rigger pre-wire
Freshwater system
Holding tank, black water
Holding tank, fresh water
Hydraulic steering (STD on 150 hp and up)
Power assisted steering
(select engines only)
Raw water wash down
Sea Water Chest w/strainer
Tilt steering
Trim tabs w/LED Indicators

CONSOLE

Changing room
Counter top, corian
Head floor, fiberglass liner
Head, electric, porcelain toilet
Head, lighting
Head, mirror
Head, wood floor
Port light window, opening
Sink w/faucet
Sky light
Tackle storage curtains
Windscreen, console
frameless glass
Windshield, Deluxe w/side entry

T-TOPS

T-Top Deluxe w/Ladder back, LED lights,
electronics box, spreader lights, & rod
holders



OPTIONS	
HULL AND DECK Gel scheme, solid color hull or two-tone, choice of Crimson Red, Denim Blue, Jet Black, Liquid Blue, Phantom Grey, or Seafoam Green Gel scheme, tri-tone, choice of Black/Atomic, Black/Crimson Red, Black/Phantom Grey, Black/White, or White/Black Gel scheme, under hardtop color, choice of Crimson Red, Denim Blue, Jet Black Liquid Blue, Phantom Grey, or Seafoam Green Ladder, dive door Rigid light Seakeeper 3, Gyro Second Helm Station (Buggy Top, Helm, Canvas, Mats, Twin HM) Second Helm Station (Buggy Top, Helm, Canvas, Mats, Triple HM) Second Helm Station (Buggy Top, Helm, Canvas, Mats, Twin JPO) Second Helm Station (Buggy Top, Helm, Canvas, Mats, Triple JPO) Underwater lights	ENGINE / SYSTEMS / DRIVE Generator VesselView Mobile, Mercury CONSOLE Head, overboard discharge Head, wood floor delete T-TOPS Outriggers, Taco grand slam CANVAS Console & helm seat cover Sail Shade w/Carbon Fiber Poles Spray shields, Eisenglass (T-Top only) PACKAGES Bow Seating Package Bow backrest cushions Bow seat cushions Offshore Package Logos & Designators, Black Mat Package, Kryptek Mat Padding, helm floor & rod storage Offshore Graphics, Black or White Premium Sound Package w/Deluxe T-Tip Fusion stereo JL Audio amplifier JL Audio speakers JL Audio subwoofer(s)
COCKPIT Air conditioning/heating Bow fill-in cushion (Req. bow cooler & table) Cockpit Reed Flooring, Ash or Dune Fishbox/Baitwell chiller Forward storage w/backrest, cushion, and cooler Grill, cockpit (Req. dockside power) Mat Package, helm floor, rod storage Refrigerator, Cockpit Rocket launchers, delete Seating, backrest, forward facing removable Storage trays, aft, tilt out Table, bow Transom seat, delete	
HELM GPS Plotter, Garmin 8622 (2) w/1KW Transducer) GPS Plotter, second helm station, Garmin 7612, 1 (Req. Garmin GPS Plotter) Night Vision, FLIR Radar, 4KW Open Array Satellite Weather (Req. GPS) Transducer, Garmin VHF radio, Garmin 315 VHF radio, Garmin 315, second helm station, w/additional handset	



NOTES



W
BAY



221 BAY



SPECIFICATIONS	US	METRIC
L.O.A	22' 4"	6.8 m
Beam	8' 6"	2.54 m
Fuel Capacity	52 Gal	197 L
Draft Up	14"	36 cm
Draft Down	27"	69 cm
Maximum Capacity	2,500 lbs	1,134 kg
Persons Capacity	8	8 CE
Approx. Boat Weight	2,900 lbs	1,315 kg
Approx. Boat & Engine Weight	3,500 lbs	1,588 kg
Max HP	250 hp	187 kw
Deadrise	15°	15°
Bridge Clearance	6' 0"	1.83 m
Bridge Clearance w/T-Top	7' 11"	2.41 m
Keel to Top of T-Top	9' 1"	2.77 m
Keel to Top of Windshield	7' 2"	2.18 m
Trailer Height w/T-Top	11' 0"	3.35 m
Trailer Height w/o T-Top	8' 11"	2.72 m

POWER RATINGS & WEIGHTS

Engine Type	Propshaft Power		Boat & Engine Weight	
	HP	KW	LBS	KG
Mercury® 150XL FourStroke	150	112	3970	1800
Mercury® 200XL FourStroke DTS	200	149	4020	1820
Mercury® 250XL Verado	250	187	4170	1890
Yamaha® F150XB	150	112	3990	1810
Yamaha® F200XB	200	149	3990	1810
Yamaha® VF250XA SHO	250	187	4060	1840
Yamaha® F250XCA	250	187	4060	1840



221B

PERFORMANCE

Power HP/ KW	Propeller (Dia x Pitch)		Type	Top Speed		Cruise Range	
	IN	CM		MPH	KPH	MI	KM
Mercury® 150XL FourStroke	15 X 17	38 X 43	AL	40-43	64-69	175	280
Mercury® 200XL FourStroke DTS	15 1/2/ X 17	39 X 43	SST	43-46	69-74	185	300
Mercury® 250XL Verado	14 5/8 X 17	37 X 43	SST	47-50	76-81	185	300
Yamaha® F150XB	15 1/4 X 15	39 X 38	AL	40-43	64-69	175	280
Yamaha® F200XB	14 1/2 X 15	37 X 38	SST	41-44	66-71	170	270
Yamaha® VF250XA SHO	15 1/4 X 19	39 X 19	SST	47-50	76-81	185	300
Yamaha® F250XCA	15 1/4 X 19	39 X 19	SST	47-50	76-81	185	300

FUEL FLOW DATA - 221B - MERCURY® 150XL FOURSTROKE

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000rpm	5	8	2	8
2500rpm	7	11	3	11
3000rpm	8	13	5	19
3500rpm	20	32	5	19
4000rpm	26	42	6	23
4500rpm	31	50	8	30
5000rpm	35	56	10	38
5500rpm	38	61	13	49
WOT	41	66	14	53

FUEL FLOW DATA - 221B - MERCURY® 200XL FOURSTROKE DTS

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000rpm	7	11	2	8
2500rpm	8	13	3	11
3000rpm	8	13	4	15
3500rpm	10	16	7	26
4000rpm	28	45	7	26
4500rpm	32	52	8	30
5000rpm	35	56	11	42
5500rpm	38	61	15	57
6000rpm	41	66	17	64
WOT	44	71	19	72

FUEL FLOW DATA - 221B - MERCURY® 250XL VERADO

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000rpm	7	11	2	8
2500rpm	8	13	3	11
3000rpm	8	13	5	19
3500rpm	11	18	9	34
4000rpm	30	48	9	34



4500 rpm	34	55	10	38
5000 rpm	38	61	14	53
5500 rpm	41	66	18	68
6000 rpm	45	72	21	97
WOT	48	77	23	87

FUEL FLOW DATA - 221B - YAMAHA® F150XB

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	5	8	2	8
2500 rpm	7	11	3	11
3000 rpm	8	13	5	19
3500 rpm	19	31	5	19
4000 rpm	25	40	6	23
4500 rpm	30	48	8	30
5000 rpm	35	56	10	38
5500 rpm	38	61	12	45
WOT	41	66	14	53

FUEL FLOW DATA - 221B - YAMAHA® F200XB

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	7	11	2	8
2500 rpm	8	13	3	11
3000 rpm	9	14	6	23
3500 rpm	19	31	6	23
4000 rpm	28	45	8	30
4500 rpm	33	53	9	34
5000 rpm	37	60	13	49
5500 rpm	40	64	17	64
WOT	43	69	18	68

FUEL FLOW DATA - 221B - YAMAHA® F250XCA & VF250XA SHO

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	7	11	3	11
2500 rpm	8	13	5	19
3000 rpm	9	14	7	26
3500 rpm	27	43	7	26
4000 rpm	31	50	9	34
4500 rpm	37	60	11	42
5000 rpm	40	64	14	53
5500 rpm	44	71	17	64
WOT	47	76	21	79

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Impeller, Boat Bottom Condition, and Operator Technique.



STANDARDS

HULL AND DECK

Anchor locker/storage
Bow and stern Eyes, stainless steel
Cleats, pull-up, stainless steel
Fiberglass stringer system
Flotation Foam
Gel scheme, all white
Gel scheme, under hardtop color, all white
Horn, stainless steel
Ladder, boarding, retractable
Meets applicable USCG & Canadian Regs;
 NMMA Certified using ABYC STDs.
Navigation Lights
Powdercoat, choice of White or Black
Rod holders, gunnel mount
Rub Rail, w/stainless steel insert
Thru hull fittings, stainless steel
Winning Edge Protection Plan

COCKPIT

5 gallon bucket in holder
Assist handles, stainless steel
Bait well/live well
Baitwell/live well, 34 gallon
 w/bluecoat, light & timer, 2
Beverage holder(s), SST
Cockpit Interior, choice of
Carbon Fiber, or Neutral w/Black Accent
Cooler, under leaning post (removable)
Courtesy Lights
Cutting station, aft
Diamond pattern non-skid
Helm seating, leaning post w/backrest,
 rod holders
Rod storage, gunnel
Seating, aft folding bench
Seating, forward console
Self bailing cockpit
Storage, bow
Storage, dry, center bow
Storage/Fishbox w/overboard drain
Tackle storage w/boxes

HELM

12 volt receptacle
Steering Wheel w/knob, stainless steel
USB charge port

ENGINE / SYSTEMS / DRIVE

Battery on/off switch
Battery tray(s)
Bilge pump, automatic
High speed live well pick-up
Hydraulic steering (STD on 150 hp and up)

CONSOLE

Changing room
Head floor, fiberglass liner
Rod holders
Tackle storage curtains
Windscreen, console,
 frameless glass



OPTIONS	
HULL AND DECK Anchor w/rope & chain Gel scheme, two-tone, choice of Crimson Red, Denim Blue, Jet Black, Liquid Blue, Phantom Grey, or Seafoam Green Gel scheme, tri-tone, choice of Black/Atomic, Black/Crimson Red, Black/Phantom Grey, Black/White, or White/Black Gel scheme, under hardtop color, choice of Crimson Red, Denim Blue, Jet Black Liquid Blue, Phantom Grey, or Seafoam Green Underwater lights	CONSOLE Head, porta pottie (NA Canada)
COCKPIT Baitwell, secondary fwd., 14 gal w/bluecoat & timer (rep. 56 qt. built in cooler) Mat Package, helm floor, rod storage Seat(s), bow fishing Seating, backrest, forward facing removable	T-TOPS T-Top Deluxe, LED lights, electronics box, spreader lights, rod holders, phone holder & Ski Tow T-Top w/rod holder & Ski Tow, Fiberglass
ENTERTAINMENT Stereo System: AM/FM w/Bluetooth* USB & MP3 port Speakers (2) Stereo System w/Deluxe T-Top: AM/FM w/Bluetooth* USB & MP3 port Speakers (4)	CANVAS Bimini Top (NA w/T-Top) Console & helm seat cover Spray shields, Eisenglass (T-Top only)
HELM Compass GPS plotter w/depth sounder, Garmin 7610 XSV	TRAILER Wellcraft custom trailer, tandem axle Galv/Gatorhyde EZ-loader aluminum, tandem axle w/brakes & spare Spare tire, aluminum or galvanized Wheels, aluminum
ENGINE / SYSTEMS / DRIVE Batteries dual w/switch Battery charger Down rigger pre-wire Jack plate, hydraulic Power assisted steering (select engines only) Power pole, port Power poles, port & stbd Raw water wash down Tilt steering Trim tabs w/LED Indicators Trolling motor pre-wire Trolling motor, 36 volt VesselView Mobile, Mercury	PACKAGES Bow Seating Package Bow seat cushions Premium Sound Package Fusion stereo JL Audio amplifier JL Audio speakers JL Audio subwoofer(s) Premium Sound Package w/Deluxe T-Top Fusion stereo JL Audio amplifier JL Audio speakers JL Audio subwoofer(s) Tournament Package Logos & Designators, Black Offshore Graphics, Black or White Mat Package, Kryptek Mat Padding, helm floor, rod storage



NOTES



241 BAY



SPECIFICATIONS	US	METRIC
L.O.A	24' 4"	7.40 m
Beam	8' 6"	2.54 m
Fuel Capacity	87 gal	329 L
Draft Up	14"	35.56 cm
Draft Down	31"	78.74 cm
Maximum Capacity	2,500 lbs	1,134 kg
Persons Capacity	8	8 CE
Approx. Boat Weight	3,700 lbs	1,678 kg
Approx. Boat & Engine Weight	4,400 lbs	1,996 kg
Max HP	300 hp	224 kw
Deadrise	15°	15°
Bridge Clearance	6' 0"	1.83 m
Bridge Clearance w/T-Top	7' 10"	2.39 m
Keel to Top of T-Top	9' 0"	2.74 m
Keel to Top of Windshield	7' 2"	2.18 m
Trailer Height w/T-Top	11' 0"	3.35 m
Trailer Height w/o T-Top	8' 11"	2.72 m

POWER RATINGS & WEIGHTS

Engine Type	Propshaft Power		Boat & Engine Weight	
	HP	KW	LBS	KG
Mercury® 200XL FourStroke DTS	200	149	4260	1930
Mercury® 250XL Verado	250	187	4420	2000
Mercury® 300XL Verado	300	224	4420	2000
Yamaha® F200XB	200	149	4240	1920
Yamaha® VF250XA SHO	250	187	4310	1950
Yamaha® F250XCA	250	187	4310	1950
Yamaha® F300XCA	300	224	4310	1950

**241B**

PERFORMANCE

Power HP/ KW	Propeller (Dia x Pitch)		Type	Top Speed		Cruise Range	
	IN	CM		MPH	KPH	MI	KM
Mercury® 200XL FourStroke DTS	15 1/2 X 17	39 X 43	SST	41-44	66-71	260	420
Mercury® 250XL Verado	14 5/8 X 17	37 X 43	SST	45-48	72-77	250	400
Mercury® 300XL Verado	14 5/8 X 17	37 X 43	SST	47-50	76-81	250	400
Yamaha® F200XB	14 1/2 X 15	37 X 38	SST	40-42	64-68	230	370
Yamaha® VF250XA SHO	15 1/2 X 17	39 X 43	SST	45-48	72-77	260	420
Yamaha® F250XCA	15 1/2 X 17	39 X 43	SST	45-48	72-77	260	420
Yamaha® F300XCA	15 1/4 X 18	39 X 46	SST	47-50	76-81	250	400

FUEL FLOW DATA - 241B - MERCURY® 200XL FOURSTROKE DTS

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000rpm	7	11	2	8
2500rpm	8	13	3	11
3000rpm	9	14	5	19
3500rpm	11	18	7	26
4000rpm	25	40	8	30
4500rpm	30	48	9	34
5000rpm	34	55	11	42
5500rpm	38	61	15	57
6000rpm	41	66	16	60
WOT	43	69	19	72

FUEL FLOW DATA - 241B - MERCURY® 250XL VERADO

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000rpm	8	13	3	11
2500rpm	9	14	6	23
3000rpm	10	16	8	30
3500rpm	18	29	9	34
4000rpm	26	42	10	38
4500rpm	31	50	12	45
5000rpm	36	58	16	60
5500rpm	41	66	20	76
6000rpm	45	72	22	83
WOT	46	74	25	95

FUEL FLOW DATA - 241B - MERCURY® 300XL VERADO

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000rpm	8	13	3	11
2500rpm	9	14	6	23
3000rpm	11	42	8	30
3500rpm	24	39	9	34
4000rpm	30	48	11	42



4500 rpm	35	56	13	49
5000 rpm	39	63	18	68
5500 rpm	43	69	22	83
6000 rpm	47	76	25	95
WOT	49	79	28	106

FUEL FLOW DATA - 241B - YAMAHA® F200XB

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	7	11	2	8
2500 rpm	8	13	3	11
3000 rpm	10	16	6	23
3500 rpm	19	31	6	23
4000 rpm	27	43	8	30
4500 rpm	31	50	9	34
5000 rpm	35	56	13	49
5500 rpm	40	64	17	64
WOT	42	68	18	68

FUEL FLOW DATA - 241B - YAMAHA® F250XCA & VF250XA SHO

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	8	13	4	15
2500 rpm	10	16	6	23
3000 rpm	23	37	7	26
3500 rpm	29	47	9	34
4000 rpm	34	55	12	45
4500 rpm	38	61	14	53
5000 rpm	42	68	19	72
5500 rpm	45	72	22	83
WOT	47	76	25	95

FUEL FLOW DATA - 241B - YAMAHA® F300XCA

Engine Speed - RPM	Boat Speed		Fuel Flow	
	MPH	KPH	GPH	LPH
2000 rpm	8	13	4	15
2500 rpm	10	16	6	23
3000 rpm	23	37	7	26
3500 rpm	30	48	10	38
4000 rpm	35	56	13	49
4500 rpm	40	64	16	60
5000 rpm	44	71	21	79
5500 rpm	47	76	25	95
WOT	49	79	29	110

Performance and Fuel Flows may vary widely due to Boat Weight, Load, Atmospheric Conditions, Engine Conditions, Weight Distribution, Sea Conditions, Impeller, Boat Bottom Condition, and Operator Technique.



STANDARDS

HULL AND DECK

- Anchor locker/storage
- Bow and stern Eyes, stainless steel
- Cleats, pull-up, stainless steel
- Fiberglass stringer system
- Flotation Foam
- Gel scheme, all white
- Gel scheme, under hardtop color, all white
- Horn, stainless steel
- Ladder, boarding, retractable
- Meets applicable USCG & Canadian Regs;
NMMA Certified using ABYC STDs.
- Navigation Lights
- Powdercoat, choice of White or Black
- Rod holders, gunnel mount
- Rub Rail, w/stainless steel insert
- Thru hull fittings, stainless steel
- Winning Edge Protection Plan

COCKPIT

- 5 gallon bucket in holder
- Assist handles, stainless steel
- Bait well/live well
- Baitwell/live well, 34 gallon w/bluecoat,
light & timer
- Beverage holder(s), SST
- Cockpit Interior, choice of
Carbon Fiber, or Neutral w/Black Accent
- Cooler, under leaning post (removable)
- Courtesy Lights
- Cutting station, aft
- Diamond pattern non-skid
- Helm seating, leaning post w/backrest,
rod holders
- Rod storage, gunnel
- Seating, aft folding bench
- Seating, forward console
- Self bailing cockpit
- Storage, bow
- Storage, dry, center bow
- Storage/Fishbox w/overboard drain
- Tackle storage w/boxes

HELM

- 12 volt receptacle
- Steering Wheel w/knob, stainless steel
- USB charge port

ENGINE / SYSTEMS / DRIVE

- Battery on/off switch
- Battery tray(s)
- Bilge pump, automatic
- High speed live well pick-up
- Hydraulic steering (STD on 150 hp and up)

CONSOLE

- Changing room
- Head floor, fiberglass liner
- Rod holders
- Tackle storage curtains
- Windscreen, console,
frameless glass



OPTIONS	
HULL AND DECK Anchor w/rope & chain Gel scheme, two-tone, choice of Crimson Red, Denim Blue, Jet Black, Liquid Blue, Phantom Grey, or Seafoam Green Gel scheme, tri-tone, choice of Black/Atomic, Black/Crimson Red, Black/Phantom Grey, Black/White, or White/Black Gel scheme, under hardtop color, choice of Crimson Red, Denim Blue, Jet Black Liquid Blue, Phantom Grey, or Seafoam Green Underwater lights	CONSOLE Head, porta pottie (NA Canada)
COCKPIT Baitwell, secondary fwd., 14 gal w/bluecoat & timer (rep. 56 qt. built in cooler) Mat Package, helm floor, rod storage Seat(s), bow fishing Seating, backrest, forward facing removable	T-TOPS T-Top Deluxe, LED lights, electronics box, spreader lights, rod holders, phone holder & Ski Tow T-Top w/rod holder & Ski Tow, Fiberglass
ENTERTAINMENT Stereo System: AM/FM w/Bluetooth* USB & MP3 port Speakers (2) Stereo System w/Deluxe T-Top: AM/FM w/Bluetooth* USB & MP3 port Speakers (4)	CANVAS Bimini Top (NA w/T-Top) Console & helm seat cover Spray shields, Eisenglass (T-Top only)
HELM Compass GPS plotter w/depth sounder, Garmin 7610 XSV	TRAILER Wellcraft custom trailer, tandem axle Galv/Gatorhyde EZ-loader aluminum, tandem axle w/brakes & spare Spare tire, aluminum or galvanized Wheels, aluminum
ENGINE / SYSTEMS / DRIVE Batteries dual w/switch Battery charger Down rigger pre-wire Jack plate, hydraulic Power assisted steering (select engines only) Power pole, port Power poles, port & stbd Raw water wash down Tilt steering Trim tabs w/LED Indicators Trolling motor pre-wire Trolling motor, 36 volt VesselView Mobile, Mercury	PACKAGES Bow Seating Package Bow seat cushions Premium Sound Package Fusion stereo JL Audio amplifier JL Audio speakers JL Audio subwoofer(s) Premium Sound Package w/Deluxe T-Top Fusion stereo JL Audio amplifier JL Audio speakers JL Audio subwoofer(s) Tournament Package Logos & Designators, Black Offshore Graphics, Black or White Mat Package, Kryptek Mat Padding, helm floor, rod storage



NOTES



182 FISHERMAN SINGLE AXLE TRAILER

SPECIFICATIONS	US	METRIC
Trailer Length w/Tongue	20' 1"	6.12 M
Trailer Length w/Tongue Folded	17' 11"	5.461 M
Width	8' 6"	2.59 M
Empty weight w/Spare	790 LBS	358 KG
Carrying Capacity	4,210 LBS	1910 KG
GVWR (Gross Vehical Weight Rating)	5,000 LBS	2,268 KG
GAWR (Gross Axle Weight Rating)	5,000 LBS	2,268 KG
Tire Size/Range (Standard)	ST 225/75R15D RADIAL	ST 225/75R15D RADIAL
Tire Pressure	65 PSI COLD	450 KPA COLD
Tire Capacity	2,540 LBS	1,152 KG
Lug Nut Torque	90-120 FT/LBS	120.6 NM-162.8NM
Axle	SINGLE	SINGLE
Axle Rating (Per Axle)	5,000 LBS	2,268 KG
Hub	6 LUG 5.5" PATTERN	6 LUG 14 CM PATTERN
Wheel Type	GALVANIZED	GALVANIZED
Jack Capacity	1,200 LBS	544 KG
Winch	1,800 LBS	818 KG
Ball Size	2"	5 CM
Ball Towing Height	24"	61 CM



202 FISHERMAN TANDEM AXLE TRAILER

SPECIFICATIONS	US	METRIC
Trailer Length w/Tongue	23'	7 M
Trailer Length w/Tongue Folded	20' 10"	6.35 M
Width	8' 6"	2.59 M
Empty weight w/Spare	1,030 LBS	467.2 KG
Carrying Capacity	5,970 LBS	2,708 KG
GVWR (Gross Vehical Weight Rating)	7,000 LBS	3,175 KG
GAWR (Gross Axle Weight Rating)	7,000 LBS	3,175 KG
Tire Size/Range (Standard)	ST 205/75R14C RADIAL	ST 205/75R14C RADIAL
Tire Pressure	50 PSI COLD	350 KPA COLD
Tire Capacity	1,760 LBS	798 KG
Lug Nut Torque	90-120 FT/LBS	120.6NM-162.8NM
Axle	TANDEM	TANDEM
Axle Rating (Per Axle)	3,500 LBS	1,588 KG
Hub	5 LUG 4.5" PATTERN	5 LUG 11CM PATTERN
Wheel Type	SILVER	SILVER
Jack Capacity	1,500 LBS	680 KG
Winch	1,800 LBS	818 KG
Ball Size	2"	5 CM
Ball Towing Height	21"	53.3 CM



222 FISHERMAN TANDEM AXLE TRAILER

SPECIFICATIONS	US	METRIC
Trailer Length w/Tongue	24' 4"	7.417 M
Trailer Length w/Tongue Folded	21' 8"	6.604 M
Width	8' 6"	2.591 M
Empty weight w/Spare	1,168 LBS	529.8 KG
Carrying Capacity	5,832 LBS	2,645 KG
GVWR (Gross Vehical Weight Rating)	7,000 LBS	3,175 KG
GAWR (Gross Axle Weight Rating)	7,000 LBS	3,175 KG
Tire Size/Range (Standard)	ST 205/75R14C RADIAL	ST 205/75R14C RADIAL
Tire Pressure	50 PSI COLD	350 KPA COLD
Tire Capacity	1,760 LBS	798 KG
Lug Nut Torque	90-120 FT/LBS	120.6NM-162.8NM
Axle	TANDEM	TANDEM
Axle Rating (Per Axle)	3,500 LBS	1,588 KG
Hub	5 LUG 4.5" PATTERN	5 LUG 11CM PATTERN
Wheel Type	GALVANIZED	GALVANIZED
Jack Capacity	1,500 LBS	680 KG
Winch	2,600 LBS	1,179 KG
Ball Size	2"	5 CM
Ball Towing Height	21"	53.3 CM



242 FISHERMAN TANDEM AXLE TRAILER

SPECIFICATIONS	US	METRIC
Trailer Length w/Tongue	27' 11"	8.509 M
Trailer Length w/Tongue Folded	23' 3	7.087 M
Width	8' 6"	2.591 M
Empty weight w/Spare	1,385 LBS	628.2 KG
Carrying Capacity	8,415 LBS	3,817 KG
GVWR (Gross Vehical Weight Rating)	9,800 LBS	4,445 KG
GAWR (Gross Axle Weight Rating)	10,000 LBS	4,535 KG
Tire Size/Range (Standard)	ST 225/75R15D RADIAL	ST 225/75R15D RADIAL
Tire Pressure	65 PSI COLD	350 KPA COLD
Tire Capacity	1,760 LBS	798 KG
Lug Nut Torque	90-120 FT/LBS	120.6NM-162.8NM
Axle	TANDEM	TANDEM
Axle Rating (Per Axle)	5,000 LBS	2,268 KG
Hub	6 LUG 5.5" PATTERN	6 LUG 14 CM PATTERN
Wheel Type	GALVANIZED	GALVANIZED
Jack Capacity	1,500 LBS	680 KG
Winch	2,600 LBS	1,179 KG
Ball Size	2 5/16"	6 CM
Ball Towing Height	24.5"	62.23 CM



221 BAY TANDEM AXLE TRAILER

SPECIFICATIONS	US	METRIC
Trailer Length w/Tongue	23' 6"	7.163 M
Trailer Length w/Tongue Folded	20' 10"	6.35 M
Width	8' 6"	2.591 M
Empty weight w/Spare	1,167 LBS	529.3 KG
Carrying Capacity	5,833 LBS	2,646 KG
GVWR (Gross Vehical Weight Rating)	7,000 LBS	3,175 KG
GAWR (Gross Axle Weight Rating)	7,000 LBS	3,175 KG
Tire Size/Range (Standard)	ST 205/75R14C RADIAL	ST 205/75R14C RADIAL
Tire Pressure	50 PSI COLD	350 KPA COLD
Tire Capacity	1,760 LBS	798 KG
Lug Nut Torque	90-120 FT/LBS	120.6NM-162.8NM
Axle	TANDEM	TANDEM
Axle Rating (Per Axle)	3,500 LBS	1,588 KG
Hub	5 LUG 4.5" PATTERN	5 LUG 11CM PATTERN
Wheel Type	GALVANIZED	GALVANIZED
Jack Capacity	1,500 LBS	680 KG
Winch	2,600 LBS	1,179 KG
Ball Size	2"	5 CM
Ball Towing Height	21"	53.3 CM



241 BAY TANDEM AXLE TRAILER

SPECIFICATIONS	US	METRIC
Trailer Length w/Tongue	25' 3"	7.696 M
Trailer Length w/Tongue Folded	22' 7"	6.883 M
Width	8' 6"	2.591 M
Empty weight w/Spare	1,211 LBS	549.3 KG
Carrying Capacity	5,789 LBS	2,626 KG
GVWR (Gross Vehical Weight Rating)	7,000 LBS	3,175 KG
GAWR (Gross Axle Weight Rating)	7,000 LBS	3,175 KG
Tire Size/Range (Standard)	ST 205/75R14C RADIAL	ST 205/75R14C RADIAL
Tire Pressure	50 PSI COLD	350 KPA COLD
Tire Capacity	1,760 LBS	798 KG
Lug Nut Torque	90-120 FT/LBS	120.6NM-162.8NM
Axle	TANDEM	TANDEM
Axle Rating (Per Axle)	3,500 LBS	1,588 KG
Hub	5 LUG 4.5" PATTERN	5 LUG 11CM PATTERN
Wheel Type	GALVANIZED	GALVANIZED
Jack Capacity	1,500 LBS	680 KG
Winch	2,600 LBS	1,179 KG
Ball Size	2"	5 CM
Ball Towing Height	21"	53.3 CM

Rec Boat Holdings, LLC dba Wellcraft ("Wellcraft") warrants to you, the first North American retail purchaser of this 2019 model year Wellcraft boat from a factory authorized dealer, or a second North American retail purchaser as noted below ("you"), that it will repair or replace, at its sole discretion, defects in materials or workmanship that occur and are reported to Wellcraft, or its factory authorized dealer, within the applicable limited warranty periods, subject to the terms, conditions and exclusions set forth below. Your acceptance of delivery of the warranted Wellcraft boat constitutes your acceptance of the terms of this limited warranty. This limited warranty gives you specific legal rights, which may vary from state to state.

This limited warranty is the sole and exclusive express warranty from Wellcraft regarding your 2019 Wellcraft boat and there are no express warranties which extend beyond those outlined in this limited warranty. There are no implied warranties from Wellcraft, unless otherwise required under applicable law, and **ALL IMPLIED OR STATUTORY WARRANTIES OR CONDITIONS (INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE) ARE EXCLUDED AND DISCLAIMED WHERE ALLOWED BY APPLICABLE LAW. ANY IMPLIED OR CONDITIONS WARRANTIES (IF APPLICABLE) ARE LIMITED TO THE MINIMUM PERIOD OF TIME ALLOWED UNDER APPLICABLE LAW. Some states do not allow limitations on how long an implied warranty lasts, so the above limitations may not apply to you.**

COVERAGE UNDER THIS LIMITED WARRANTY

Exterior Cosmetic Gel Coat Limited Warranty: The limited warranty period runs for one (1) year for defects in the boat's exterior cosmetic gel coat, including cracking, crazing, discoloring and fading, except as noted below.

Non-Structural Parts And Components Limited Warranty: The limited warranty period runs for three (3) years for defects in non-structural parts and components, except as noted below. All Non-Structural Hull and Component warranty repairs are subject to a \$100 deductible per warranty claim for years 2 and 3.

Osmotic Hull Blister Limited Warranty: The limited warranty period to the first North American retail purchaser runs for five (5) years, except as noted below, for osmotic Hull (defined below) blisters on the boat, which are defined as blisters larger than 1/8" diameter and with a depth of 1/16" or greater, which occur on the boat Hull below the waterline. This limited warranty is not transferable.

If the boat is bottom painted or left in water for more than sixty (60) days in any 90 day period, this limited warranty will only apply if a marine barrier coating with proper surface preparation is applied to the boat Hull before it is bottom painted or left in the water for more than sixty (60) days in any ninety (90) day period.

In the event of osmotic blistering, Wellcraft must approve of any repairs, and their method and cost, **before** the repairs are performed, for this limited warranty to apply. Once any repairs are completed, a marine barrier coating must be applied to the affected Hull surface area(s).

Repairs under this osmotic Hull blister limited warranty are limited to one time. Any repair costs covered under this limited warranty are limited to labor and materials only. They will be paid on a prorated basis, according to the schedule outlined below. The repair costs cannot exceed \$150 (US) per foot of boat length prior to the prorating outlined below:

Osmotic Hull blistering reported to Wellcraft:	Amount of repair costs paid:
Less than two (2) years from date of delivery	100%
Two (2) to less than three (3) years from date of delivery	75%
Three (3) to less than four (4) years from date of delivery	50%
Four (4) to five (5) years from date of delivery	25%

Structural Deck Or Liner Limited Warranty: The limited warranty period runs for five (5) years for Structural Deck or Liner Defects (defined below), except as noted below. For purposes of this limited warranty, the "Deck" shall mean the single fiberglass molded shell and integral fiberglass structural components above the Hull (defined below) flange (i.e. gunwale) and the "Liner" shall mean the single fiberglass molded interior shell walls and interior floor of the Hull (defined below) below the Hull flange (i.e. gunwale). A "Structural Deck or Liner Defect" shall mean a substantial defect in the boat's Hull or Liner which causes the boat to be unfit or unsafe for use as a pleasure craft under normal operating conditions.

Structural Hull Limited Warranty: The limited warranty period runs for ten (10) years for Structural Hull Defects (defined below), except as noted below. For purposes of this limited warranty, the "Hull" shall mean the single fiberglass molded shell and integral structure within the shell, including stringers, floorboards, transom and related structural reinforcements, all of which are below the Hull flange (i.e. gunwale). A "Structural Hull Defect" shall mean a defect that causes the Hull to be unsafe or unfit for use under normal operating conditions.

The applicable limited warranty period, for both the First and Second (if applicable) North American retail purchasers, runs from the date of delivery of the boat to the first North American retail purchaser, provided that the boat is delivered to that purchaser within twelve (12) months from the date of its manufacture. For a boat delivered to that purchaser more than twelve (12) months after the date of its manufacture, the limited warranty period runs from the date of its manufacture, not from the date the boat was delivered to the first North American retail purchaser. For a boat delivered to that purchaser more than twelve (12) months and up to thirty-six (36) months after its date of manufacture, the selling dealer will be required to submit a condition report on the boat with photos to Wellcraft before delivery of the boat to that purchaser; Wellcraft will then determine and advise what limited warranty coverage remains in effect on the boat, if any. For a boat delivered to that purchaser more than thirty-six (36) months after the date of its manufacture, only the structural limited warranties on the boat will be in effect; all other limited warranties are voided. All limited warranties run concurrently.

This limited warranty may be transferred to a second North American retail purchaser, if the transfer occurs within five (5) years of the boat's sale to the first North American retail purchaser, for a non-refundable recording fee of \$300 (US), provided that the second North American retail purchaser purchases the boat from the first North American retail purchaser or an authorized Wellcraft dealer. To transfer the limited warranty, the second North American retail purchaser or the authorized Wellcraft dealer must send to Wellcraft, within fifteen (15) days of the boat's purchase, at the address noted below the: 1) first North American retail purchaser's plastic registration card, if available; 2) proof of purchase; and 3) the non-refundable recording fee made payable to Rec Boat Holdings, LLC dba Wellcraft. The limited warranty may only be transferred **once**. Wellcraft will confirm all limited warranty transfers, in writing, to the authorized Wellcraft dealer and/or second North American retail purchaser via email. Wellcraft reserves the right to reject a limited warranty transfer request for a Wellcraft boat that has been damaged, neglected or otherwise previously excluded from limited warranty coverage.

THIS LIMITED WARRANTY DOES NOT COVER

1. A boat originally purchased from any party other than an authorized Wellcraft dealer or the first North American retail purchaser.
2. A boat, including its components, that has been altered or modified so as to adversely affect its operation, performance or durability, as determined by Wellcraft, or a boat that has been salvaged or declared a total loss or a constructive total loss for any reasons not covered in this limited warranty.
3. Any damage resulting from an accident or impact with another object, or any damage caused by an act of nature.



4. Damage, breakage and leakage around windshields, hatches or other designed openings.
5. Boats that are damaged due to storage, environmental or exposure conditions including, but not limited to, sun or cold weather.
6. Engines, power trains, generators, air conditioners, outdrives, jet pumps, controls, propellers, batteries, appliances and other equipment, accessories or components that are not manufactured by Wellcraft, whether or not they are warranted by other manufacturers. **Note:** it is the purchaser's responsibility to complete any limited warranty registration procedure that may be applicable to these components. **Note: dealers are expected to properly represent the engine brands offered in ordered units through service training certification, parts support, warranty access, etc.**
7. Window glass, mirrors, varnish, paint, fabrics and chromium, stainless steel and other metal finishes.
8. Gel coat fading or discoloration that occurs below or at the water line on the Hull.
9. Any original gel surface that has been altered in any way, including by repair, application of any coating other than marine barrier coating or marine barrier coating followed by bottom paint, improper surface preparation for paint or improper or excessive sanding, scraping or sandblasting.
10. The cost of removal or re-installation of parts or disassembly of units to repair or replace components covered by this limited warranty.
11. A boat that has been overpowered, according to the boat's maximum recommended engine horsepower, or overloaded in excess of the maximum limits as stated on the U.S. Coast Guard Capacity Plate.
12. Any boat that has been misused; used in a negligent manner; used for racing, speed or endurance contests; used as a rental or charter boat; used for military, rescue, fire, safety, medical, police, law enforcement, patrol or similar government uses; used for commercial purposes; used without normal maintenance; operated contrary to any instructions furnished by Wellcraft; improperly lifted or trailered; improperly secured to a trailer; or operated in violation of any federal, state, local, Coast Guard or other governmental agency laws, rules or regulations. Also, this limited warranty does not cover any damage resulting from failure to use a lower unit support device on any boat with an outboard motor when transporting the boat.
13. Estimated characteristics such as weight, speed, range, fuel consumption or other estimated performance characteristics.
14. Dealer preparation, cleaning, final adjustments and alignments in preparing the boat for delivery.
15. Fit and adjustment of exterior canvas tops, enclosures and weather covers or other soft goods.
16. Sacrificial deterioration of anti-fouling paint or zinc anodes.
17. Damage resulting from electrolysis or corrosion of any nature from any source.
18. Any failure or defect arising from previous repairs made by a non-authorized service provider, unless preapproved by Wellcraft.
19. Any defect that results in redesign of the Wellcraft boat.
20. Trailers (non-Wellcraft brand).

THE SOLE AND EXCLUSIVE REMEDY UNDER THIS LIMITED WARRANTY AND ANY APPLICABLE IMPLIED WARRANTY OR CONDITION (IF ANY) IS THE REPAIR OR REPLACEMENT, AT WELLCRAFT'S SOLE OPTION, OF WARRANTED PARTS AND COMPONENTS.



WELLCRAFT EXCLUDES AND DISCLAIMS ANY LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES, INCLUDING LOSS OF TIME, INCONVENIENCE, INSTALLMENT PAYMENTS, INSURANCE PAYMENTS, MARINA FEES, RETAIL CHARGES, TRAVEL EXPENSES, LOSS OF USE, HAUL OUT, LAUNCH, TOWING AND/OR STORAGE CHARGES, LOSS OF OR DAMAGE TO PERSONAL PROPERTY OR OTHER SIMILAR COSTS AND EXPENSES OR ANY CLAIM NOT SPECIFICALLY COVERED BY THIS LIMITED WARRANTY. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. Any legal action alleging breach of any applicable warranty coverage must be brought within one (1) year from the date the alleged breach first occurred or the shortest period allowed under applicable law, whichever is earlier.

PRE-DELIVERY SERVICE AND LIMITED WARRANTY REGISTRATION

Prior to delivering a new Wellcraft boat to the first North American retail purchaser, the authorized dealer is required to inspect and perform all necessary pre-delivery services including completing the "Pre-Delivery Service Record" portion of the limited warranty. Any cost associated with the pre-delivery inspection is the responsibility of the first North American retail purchaser. After completion of the necessary pre-delivery services, the first North American retail purchaser must sign the Wellcraft limited warranty registration form and Pre-Delivery Service Record provided by the dealer, where indicated. No limited warranty coverage is applicable to the boat unless these forms are completed, signed and returned to Wellcraft at the address indicated below, or via an authorized Wellcraft dealer's online dealer extranet. All information received by Wellcraft via the limited warranty registration or transfer process shall be the property of Wellcraft, and submission of information, directly or indirectly, via the limited warranty registration process shall, to the extent permitted by applicable law, be deemed to constitute consent by the purchaser and dealer to Wellcraft's use of such information at any time for all purposes allowed by law, including use of that information by third parties selected by Wellcraft. You may opt to not have your personal information disclosed to third parties and/or to not receive marketing materials from Wellcraft by sending a written request to: Wellcraft Warranty Department, 925 Frisbie Street, Cadillac, MI 49601.

OBTAINING REPAIRS UNDER THIS LIMITED WARRANTY

The authorized Wellcraft dealer will carry out the limited warranty procedures on your behalf. All limited warranty work must be performed at an authorized dealer or a sublet repair facility chosen by an authorized dealer, at the Wellcraft factory, or at another repair facility approved by Wellcraft. You are responsible for the expense associated with transporting the boat to and from the repair facility. Wellcraft must receive written notice of all limited warranty claims prior to the expiration of this limited warranty and be allowed an opportunity to resolve them.

To obtain limited warranty service, you must return the boat, including any alleged defective part, to an authorized Wellcraft dealer and present the Owner's Registration Card. If necessary, you should call Wellcraft for assistance to locate the nearest Wellcraft dealer in your area. The following procedures will apply to a limited warranty claim:

- A. The dealer will contact and receive an authorization number from Wellcraft for repairs.
- B. Upon completion of repairs, you must pay the dealer for non-covered items and any applicable deductible.
- C. You assume all liability for payment of non-authorized repairs.
- D. You must sign the Wellcraft limited warranty claim form if the claim is not submitted through the Wellcraft extranet by the dealer.

If sublet limited warranty repairs are required for any reason, the authorized Wellcraft dealer will be responsible for choosing a qualified and reputable repair facility and the authorized **Wellcraft Dealer will be responsible for all work performed by the sublet repair facility.**



Before referring any work to a sublet repair facility, the authorized Wellcraft dealer must submit a written estimate to Wellcraft's claims department to obtain written pre-authorization (including a claim authorization number). Wellcraft will not honor or pay for claims submitted for repairs by sublet repair facilities unless this procedure has been followed. Wellcraft will not authorize or pay for sublet repairs initiated because of a lack of dealer service facilities.

This document contains the entire limited warranty provided by Wellcraft. Any questions concerning the scope of this limited warranty should be directed to Wellcraft. The terms and conditions contained in this limited warranty may not be modified, altered or waived by any action, inaction or representation, whether oral or in writing, except upon the express, written authority of a senior management level employee of Wellcraft. Wellcraft does not authorize any person or persons (except a senior management level employee of Wellcraft), including Wellcraft's dealers, to change the terms of this limited warranty. (Note that your authorized Wellcraft dealer is an independent business, authorized to sell and service Wellcraft products, but is not an agent of Wellcraft). Wellcraft reserves the right to change or improve the design or manufacture of Wellcraft boats without obligation to modify any boat previously manufactured.

Wellcraft
925 Frisbie Street
Cadillac, MI 49601
Telephone: 231-775-1351



NOTES

Rec Boat Holdings, LLC dba Wellcraft ("Wellcraft") warrants to you, the first International retail purchaser of this 2019 model year Wellcraft boat from a factory authorized dealer, or a second International retail purchaser as noted below ("you"), that it will repair or replace, at its sole discretion, defects in materials or workmanship that occur and are reported to Wellcraft, or its factory authorized dealer, within the applicable limited warranty periods, subject to the terms, conditions and exclusions set forth below. Your acceptance of delivery of the warranted Wellcraft boat constitutes your acceptance of the terms of this limited warranty.

This limited warranty is the sole and exclusive express warranty from Wellcraft regarding your 2019 Wellcraft boat, and there are no express warranties which extend beyond those outlined in this limited warranty. There are no implied warranties from Wellcraft unless otherwise required under applicable law, and ALL IMPLIED OR STATUTORY WARRANTIES OR CONDITIONS (INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE) ARE EXCLUDED AND DISCLAIMED WHERE ALLOWED BY APPLICABLE LAW. ANY IMPLIED OR CONDITIONS WARRANTIES (IF APPLICABLE) ARE LIMITED TO THE MINIMUM PERIOD OF TIME ALLOWED UNDER APPLICABLE LAW. Retail purchasers in the European Union (EU) may have legal rights under applicable national legislation and the Consumers Protective Directive 1999/44/EC of the European Parliament and of the Council of 25 May 1999, governing the sale of consumer goods, which are not affected by this limited warranty. Retail purchasers in other countries may also have legal rights which are not affected by this limited warranty.

COVERAGE UNDER THIS LIMITED WARRANTY

Exterior Cosmetic Gel Coat Limited Warranty: The limited warranty period runs for one (1) year for defects in the boat's exterior cosmetic gel coat, including cracking, crazing, discoloring and fading, except as noted below.

Non-Structural Parts And Components Limited Warranty: The limited warranty period runs for one (1) year for defects in non-structural parts and components, except as noted below.

Structural Deck Or Liner Limited Warranty: The limited warranty period runs for five (5) years for Structural Deck or Liner Defects (defined below), except as noted below. For purposes of this limited warranty, the "Deck" shall mean the single fiberglass molded shell and integral fiberglass structural components above the Hull flange (i.e. gunwale) and the "Liner" shall mean the single fiberglass molded interior shell walls and interior floor of the Hull (defined below) below the Hull flange (i.e. gunwale). A "Structural Deck or Liner Defect" shall mean a substantial defect in the boat's Hull or Liner, which causes the boat to be unfit or unsafe for use as a pleasure craft under normal operating conditions.

Structural Limited Warranty: The limited warranty period runs for ten (10) years for Structural Hull Defects, except as noted below. For purposes of this limited warranty, the "Hull" shall mean the single fiberglass molded shell and integral structure within the shell, including stringers, floorboards, transom and related structural reinforcements, all of which are below the Hull flange (i.e. gunwale). A "Structural Hull Defect" shall mean a defect that causes the Hull to be unsafe or unfit for use under normal operating conditions.

The applicable limited warranty period, for both the first and second (if applicable) International retail purchasers, runs from the date of delivery of the boat to the first International retail purchaser, provided that the boat is delivered to that purchaser within twelve (12) months from the date of its manufacture. For a boat delivered to that purchaser more than twelve (12) months after the date of its manufacture, the limited warranty period runs from the date of its manufacture, not from the date the boat was delivered to the first International retail purchaser. For a boat delivered to that purchaser more than twelve (12) months and up to thirty-six (36) months after its date of manufacture, the selling dealer will be required to submit a condition report on the boat with photos to Wellcraft before delivery of the boat to that purchaser; Wellcraft will then determine and advise what limited

warranty coverage remains in effect on the boat, if any. For a boat delivered to that purchaser more than thirty-six (36) months after the date of its manufacture, only the structural limited warranties on the boat will be in effect; all other limited warranties are voided. All limited warranties run concurrently.

This limited warranty may be transferred to a second International retail purchaser, if the transfer occurs within five (5) years of the boat's sale to the first International retail purchaser, for a non-refundable recording fee of \$300 (US) provided that the second International retail purchaser purchases the boat from the first International retail purchaser or an authorized Wellcraft dealer. To transfer the limited warranty, the second International retail purchaser or the authorized Wellcraft dealer must send to Wellcraft, within fifteen (15) days of the boat's purchase, at the address noted below the: 1) first International retail purchaser's plastic registration card, if available; 2) proof of purchase; and 3) the non-refundable recording fee made payable to Wellcraft. The limited warranty may only be transferred **once**. Wellcraft will confirm all limited warranty transfers, in writing, to the authorized Wellcraft dealer and/or second International retail purchaser via email. Wellcraft reserves the right to reject a limited warranty transfer request for a Wellcraft boat that has been damaged, neglected or otherwise previously excluded from limited warranty coverage.

THIS LIMITED WARRANTY DOES NOT COVER

1. A boat originally purchased from any party other than an authorized Wellcraft dealer or the first International retail purchaser.
2. A boat, including its components, that has been altered or modified so as to adversely affect its operation, performance or durability, as determined by Wellcraft, or a boat that has been salvaged or declared a total loss or a constructive total loss for any reasons not covered in this limited warranty.
3. Any damage resulting from an accident or impact with another object or any damage caused by an act of nature.
4. Damage, breakage and leakage around windshields, hatches or other designed openings.
5. Boats that are damaged due to storage, environmental or exposure conditions including, but not limited to, sun or cold weather.
6. Engines, power trains, generators, air conditioners, outdrives, jet pumps, controls, propellers, batteries, appliances and other equipment, accessories or components that are not manufactured by Wellcraft, whether or not they are warranted by other manufacturers. **Note:** it is the purchaser's responsibility to complete any limited warranty registration procedure that may be applicable to these components. **Note: dealers are expected to properly represent the engine brands offered in ordered units through service training, parts support, warranty access, etc.**
7. Window glass, mirrors, varnish, paint, fabrics and chromium, stainless steel and other metal finishes.
8. Gel coat fading or discoloration that occurs below or at the water line on the Hull.
9. Gel coat damage resulting from blistering and osmotic blistering; any original gel surface that has been altered in any way, including by repair, application of any coating other than marine barrier coating or marine barrier coating followed by bottom paint, improper surface preparation for paint or improper or excessive sanding, scraping or sandblasting.
10. The cost of removal or re-installation of parts or disassembly of units to repair or replace components covered by this limited warranty.
11. A boat that has been overpowered, according to the boat's maximum recommended engine horsepower, or overloaded in excess of the maximum limits as stated on the Capacity Plate.



12. Any boat that has been misused or used in a negligent manner; used for racing, speed or endurance contests; used as a rental or charter boat; used for military, rescue, fire, safety, medical, police, law enforcement, patrol or similar government uses; used for commercial purposes; used without normal maintenance; operated contrary to any instructions furnished by Wellcraft; improperly lifted or trailered; improperly secured to a trailer; or operated in violation of any federal, state, local or governmental agency laws, rules or regulations. Also, this limited warranty does not cover any damage resulting from failure to use a lower unit support device on any boat with an outboard motor when transporting the boat.
13. Estimated characteristics such as weight, speed, range, fuel consumption or other estimated performance characteristics.
14. Dealer preparation, cleaning, final adjustments and alignments in preparing the boat for delivery.
15. Fit and adjustment of exterior canvas tops, enclosures and weather covers or other soft goods.
16. Sacrificial deterioration of anti-fouling paint or zinc anodes.
17. Damage resulting from electrolysis or corrosion of any nature from any source.
18. Any failure or defect arising from previous repairs made by a non-authorized service provider, unless preapproved by Wellcraft.
19. Any defect that results in redesign of the Wellcraft boat.
20. Trailers.

THE SOLE AND EXCLUSIVE REMEDY UNDER THIS LIMITED WARRANTY AND ANY APPLICABLE IMPLIED WARRANTY OR CONDITION (IF ANY) IS THE REPAIR OR REPLACEMENT, AT WELLCRAFT'S SOLE OPTION, OF WARRANTED PARTS AND COMPONENTS. WELLCRAFT EXCLUDES AND DISCLAIMS ANY LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES, INCLUDING LOSS OF TIME, INCONVENIENCE, INSTALLMENT PAYMENTS, INSURANCE PAYMENTS, MARINA FEES, RETAIL CHARGES, TRAVEL EXPENSES, LOSS OF USE, HAUL OUT, LAUNCH, TOWING AND/OR STORAGE CHARGES, LOSS OF OR DAMAGE TO PERSONAL PROPERTY OR OTHER SIMILAR COSTS AND EXPENSES OR ANY CLAIM NOT SPECIFICALLY COVERED BY THIS LIMITED WARRANTY. Any legal action alleging breach of any applicable warranty coverage must be brought within one (1) year from the date the alleged breach first occurred or the shortest period of time allowed under applicable law.

PRE-DELIVERY SERVICE AND LIMITED WARRANTY REGISTRATION

Prior to delivering a new Wellcraft boat to the first International retail purchaser, the authorized dealer is required to inspect and perform all necessary pre-delivery services including completing the "Pre-Delivery Service Record" portion of the limited warranty. Any cost associated with the pre-delivery inspection is the responsibility of the first International retail purchaser. After completion of the necessary pre-delivery services, the first International retail purchaser must sign the Wellcraft limited warranty registration form and Pre-Delivery Service Record provided by the dealer, where indicated. No limited warranty coverage is applicable to the boat unless these forms are completed, signed and returned to Wellcraft at the address indicated below, or via an authorized Wellcraft dealer's online dealer extranet. All information received by Wellcraft via the limited warranty registration or transfer process shall be the property of Wellcraft, and submission of information, directly or indirectly, via the limited warranty registration process shall, to the extent permitted by applicable law, be deemed to constitute consent by the purchaser and dealer to Wellcraft's use of such information at any time for all purposes allowed by law, including use of that information by third parties selected by Wellcraft.



You may opt to not have your personal information disclosed to third parties and/or to not receive marketing materials from Wellcraft by sending a written request to: Wellcraft Warranty Department, 925 Frisbie Street, Cadillac, MI 49601.

OBTAINING REPAIRS UNDER THIS LIMITED WARRANTY

The authorized Wellcraft dealer will carry out the limited warranty procedures on your behalf. All limited warranty work must be performed at an authorized dealer or a sublet repair facility chosen by an authorized dealer, at the Wellcraft factory, or at another repair facility approved by Wellcraft. You are responsible for the expense associated with transporting the boat to and from the repair facility. Wellcraft must receive written notice of all limited warranty claims prior to the expiration of this limited warranty and be allowed an opportunity to resolve them.

To obtain limited warranty service, you must return the boat, including any alleged defective part, to an authorized Wellcraft dealer and present the Owner's Registration Card. If necessary, you should call Wellcraft for assistance to locate the nearest Wellcraft dealer in your area. The following procedures will apply to a warranty claim:

- A. The dealer will contact and receive an authorization number from Wellcraft for repairs.
- B. Upon completion of repairs, you must pay the dealer for non-covered items.
- C. You assume all liability for payment of non-authorized repairs.
- D. You must sign the Wellcraft limited warranty claim form if the claim is not submitted through the Wellcraft extranet by the dealer.

If sublet limited warranty repairs are required for any reason, the authorized Wellcraft dealer will be responsible for choosing a qualified and reputable repair facility and the authorized **Wellcraft Dealer will be responsible for all work performed by the sublet repair facility. Before referring any work to a sublet repair facility, the authorized Wellcraft dealer must submit a written estimate to Wellcraft's claims department to obtain written pre-authorization (including a claim authorization number).** Wellcraft will not honor or pay for claims submitted for repairs by sublet repair facilities unless this procedure has been followed. Wellcraft will not authorize or pay for sublet repairs initiated because of a lack of dealer service facilities.

This document contains the entire limited warranty provided by Wellcraft. Any questions concerning the scope of this limited warranty should be directed to Wellcraft. The terms and conditions contained in this limited warranty may not be modified, altered or waived by any action, inaction or representation, whether oral or in writing, except upon the express, written authority of a senior management level employee of Wellcraft. Wellcraft does not authorize any person or persons (except a senior management level employee of Wellcraft), including Wellcraft's dealers, to change the terms of this limited warranty. (Note that your authorized Wellcraft dealer is an independent business, authorized to sell and service Wellcraft products, but is not an agent of Wellcraft). Wellcraft reserves the right to change or improve the design or manufacture of Wellcraft boats without obligation to modify any boat previously manufactured.

Wellcraft
925 Frisbie Street
Cadillac, MI 49601
Telephone: 231-775-1351



NOTES



925 Frisbie Street | Cadillac, MI 49601
231.775.1351

www.wellcraft.com

090-3021-19